



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Snow Drift
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact Aerolight XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SEATPOST	Giant D-Fuse, composite, -5/+15mm offset
SADDLE	Giant Grit
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano GRX RX-820, 2x12
FRONT DERAILLEUR	Shimano GRX RX-820
REAR DERAILLEUR	Shimano GRX RX-820
BRAKES	Shimano GRX RX-820 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
BRAKE LEVERS	Shimano GRX RX-820 hydraulic
CASSETTE	Shimano CS-HG710, 12-speed, 11x36
CHAIN	KMC X12L-1
CRANKSET	Shimano GRX RX-820, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant CXR 2 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
HUBS	[F] Giant alloy, CenterLock, 12mm thru-axle [R] Giant alloy, 3-pawl 36t driver, CenterLock, 12mm thru-axle
SPOKES	Sapim Sprint
TIRES	CADEX GX, 700x40c, tubeless
EXTRAS	Tubeless prepared, 53mm max tyre size in "long" flip chip position, 45mm max tyre size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TYRE CLEARANCE	53mm

Price: \$5,199.00

GEOMETRY

FRAME	XS	S	M	ML	L	XL
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	540	550	560	575	585	600
Head Tube Length (mm)	125	135	150	165	180	195
Head Tube Angle	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65
Wheelbase (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051	1051
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435	425
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	407
Stand Over Height (mm)	724 731	740 747	757 764	774 780	791 797	807
Stem Length (mm)	50	60	70	80	80	90
Crank Length (mm)	170	170	172.5	172.5	175	175

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.