

ANTHEM ADVANCED SL 1

GIANT



SPECS

RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Rainbow Black/Rainbow Charcoal
RAM	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
GAFFEL	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
BAKDÄMPARE	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTER	
STYRE	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GREPPAR	SRAM TwistLoc Ultimate
STAM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SADELSTOLPE	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel
SADEL	Giant Grit SL
PEDALER	N/A
DRIVLINA	
VÄXLAR	SRAM AXS Pod, discrete clamp, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	SRAM GX AXS Transmission
BROMSAR	Shimano Deore XT BR-M8220, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
BROMSSPAKAR	Shimano Deore XT BL-M8200
KASSETT	SRAM XS 1275, 10x52
KEDJA	SRAM GX Transmission
VEVPARTI	SRAM GX Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant XCR WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EKRAR	Carbon
DÄCK	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAFUNKTIONER	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Price: 81 990,00 kr

GEOMETRY

RAM	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Längd sadelrör (mm)	400	420	465	495
Vinkel sadelrör	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°
Topprörets längd (mm)	576 574	602 600	624 623	651 650
Styrhuvud Längd (mm)	90	95	105	115
Vinkel styrhuvud	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°
Gaffelvinkel (mm)	44	44	44	44
Spår (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2
Hjulbas (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Kedjestagslängd (mm)	437 435	437 435	437 435	437 435
Nedre fäste Drop (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Stå över höjden (mm)	769 775	764 771	758 763	751 758
Styrets bredd (mm)	780	780	780	780
Stamlängd (mm)	60	70	70	80
Vevlängd (mm)	170	170	175	175

All specifications listed are subject to change without notice.