ANTHEM ADVANCED SL 2



SPECS

RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Mariana Blue/Icicle White
RAM	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
GAFFEL	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
BAKDÄMPARE	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTER	
STYRE	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GREPPAR	SRAM TwistLoc Ultimate
STAM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SADELSTOLPE	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel /
SADEL	Giant Grit
PEDALER	N/A
DRIVLINA	
VÄXLAR	SRAM Eagle 90 mechanical, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	SRAM Eagle 90 Transmission
BROMSAR	Shimano SLX BR-M6220, hydraulic, Giant RT66 rotors [F]180mm, [R]160mm
BROMSSPAKAR	Shimano SLX BL-M6200
KASSETT	SRAM 70 1270, 10x52
KEDJA	SRAM 70 Transmission
VEVPARTI	SRAM 90 Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant XCA WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EKRAR	Sapim
DÄCK	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAFUNKTIONER	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Price: 63 990,00 kr

GEOMETRY

RAM	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Längd sadelrör (mm)	400	420	465	495
Vinkel sadelrör	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°
Topprörets längd (mm)	576 | 574	602 | 600	624 | 623	651 | 650
Styrhuvud Längd (mm)	90	95	105	115
Vinkel styrhuvud	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°
Gaffelvinkel (mm)	44	44	44	44
Spår (mm)	116 | 112,2	115,9 | 112,2	115,9 | 112,2	115,8 | 112,2
Hjulbas (mm)	1141 | 1140	1168 | 1167	1192 | 1191	1221 | 1220
Kedjestagslängd (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Nedre fäste Drop (mm)	51 | 45	51 | 45	52 | 45	52 | 45
Stack (mm)	602 | 599	607 | 603	616 | 612	626 | 622
Reach (mm)	420 | 425	445 | 450	465 | 470	490 | 495
Stå över höjden (mm)	769 | 775	764 | 771	758 | 763	751 | 758
Styrets bredd (mm)	780	780	780	780
Stamlängd (mm)	60	70	70	80
Vevlängd (mm)	170	170	175	175

All specifications listed are subject to change without notice.