

ANTHEM ADVANCED SL 3



SPECS

RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Carbon/Moon Dust
RAM	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
GAFFEL	Fox 34 SL Performance, 120mm, GRIP damper, Boost 15x110, 44mm offset, remote lockout
BAKDÄMPARE	Fox Float SL Performance Elite, 3-position damper, 210/50, 3-position lockout
KOMPONENTER	
STYRE	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GREPPAR	Giant XC Pro, silicone
STAM	Giant Integrated XC Alloy S:60mm, M:70mm, L:70mm, XL:80mm
SADELSTOLPE	Giant Core dropper, remote S: 100mm travel / 30.9 x 395mm M: 120mm travel / 30.9 x 395mm L: 120mm travel / 30.9 x
SADEL	Giant Grit
PEDALER	N/A
DRIVLINA	
VÄXLAR	Shimano Deore mechanical, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	Shimano Deore
BROMSAR	Shimano BR-MT500, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
BROMSSPAKAR	Shimano BL-MT501
KASSETT	Shimano M6100, 10x51
KEDJA	KMC X-12
VEVPARTI	Praxis Cadet HD M24, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BROMSREGLAGE	Praxis, press fit

HJUL	
FÄLGAR	Giant XCA 29 WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EKRAR	Sapim
DÄCK	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAFUNKTIONER	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Price: 52 990,00 kr

GEOMETRY

RAM	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Längd sadelrör (mm)	400	420	465	495
Vinkel sadelrör	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°
Topprörets längd (mm)	576 574	602 600	624 623	651 650
Styrhuvud Längd (mm)	90	95	105	115
Vinkel styrhuvud	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°
Gaffelvinkel (mm)	44	44	44	44
Spår (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2
Hjulbas (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Kedjestagslängd (mm)	437 435	437 435	437 435	437 435
Nedre fäste Drop (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Stå över höjden (mm)	769 775	764 771	758 763	751 758
Styrets bredd (mm)	780	780	780	780
Stamlängd (mm)	60	70	70	80
Vevlängd (mm)	170	170	175	175

All specifications listed are subject to change without notice.