

ANTHEM X ADVANCED SL 1

GIANT



SPECS

RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Solar Prominence
RAM	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
GAFFEL	Fox 34 SL Performance Elite, 130mm, GRIP X damper, Boost 15x110, 44mm offset
BAKDÄMPARE	Fox Float SL Factory, 210/50
KOMPONENTER	
STYRE	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GREPPAR	Giant Tactal, lock on
STAM	Giant Integrated XC Carbon S:50mm, M:50mm, L:60mm, XL:70mm
SADELSTOLPE	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SADEL	Giant Grit SL
PEDALER	N/A
DRIVLINJA	
VÄXLAR	SRAM AXS Pod, discrete clamp, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	SRAM GX AXS Transmission
BROMSAR	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-MT905 rotors [F]203mm, [R]180mm
BROMSSPAKAR	Shimano Deore XT BL-M8100
KASSETT	SRAM XS 1275, 10x52
KEDJA	SRAM GX Transmission
VEVPARTI	SRAM GX Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant XCR WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EKRAR	Carbon
DÄCK	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRAFUNKTIONER	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Price: 82 000,00 kr

GEOMETRY

RAM	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Längd sadelrör (mm)	400	420	465	495
Vinkel sadelrör	75,0° 75,5°	75,1° 75,5°	75,1° 75,6°	75,1° 75,6°
Topprörets längd (mm)	577 575	603 602	625 624	653 651
Styrhuvud Längd (mm)	90	95	105	115
Vinkel styrhuvud	66,0° 66,5°	66,1° 66,5°	66,1° 66,6°	66,1° 66,6°
Gaffelvinkel (mm)	44	44	44	44
Spår (mm)	119,5 115,7	119,3 115,6	119,2 115,5	119 115,4
Hjulbas (mm)	1145 1144	1172 1171	1196 1195	1225 1224
Kedjestagslängd (mm)	437 435	437 435	437 435	437 435
Nedre fäste Drop (mm)	48 42	48 42	48 42	48 42
Stack (mm)	606 602	611 607	620 616	629 625
Reach (mm)	415 420	440 445	460 465	485 490
Stå över höjden (mm)	774 780	770 776	762 769	757 764
Styrets bredd (mm)	780	780	780	780
Stamlängd (mm)	50	50	60	70
Vevlängd (mm)	170	170	175	175

All specifications listed are subject to change without notice.