# ANTHEM X ADVANCED SL 2




## SPECS

| RAM | |
|---|---|
| **STORLEKAR** | S, M, L, XL |
| **FÄRGER** | Dark Jungle |
| **RAM** | Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage |
| **GAFFEL** | Fox 34 SL Performance, 130mm, GRIP damper, Boost 15x110, 44mm offset |
| **BAKDÄMPARE** | Fox Float SL Performance, 210/50 |
| **KOMPONENTER** | |
| **STYRE** | Giant Integrated XC, alloy, 780mm, 9-degree upsweep |
| **GREPPAR** | Giant Tactal, lock on |
| **STAM** | Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm |
| **SADELSTOLPE** | Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm |
| **SADEL** | Giant Grit |
| **PEDALER** | N/A |
| **DRIVLINA** | |
| **VÄXLAR** | SRAM Eagle 90 mechanical, 1x12 |
| **FRAMVÄXEL** | N/A |
| **BAKVÄXEL** | SRAM Eagle 90 Transmission |
| **BROMSAR** | Shimano SLX BR-M7120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm |
| **BROMSSPAKAR** | Shimano SLX BL-M7100 |
| **KASSETT** | SRAM 70 1270, 10x52 |
| **KEDJA** | SRAM 90 Transmission |
| **VEVPARTI** | SRAM 90 Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm |
| **BROMSREGLAGE** | SRAM DUB, press fit |

| HJUL | |
|---|---|
| **FÄLGAR** | Giant XCA WheelSystem |
| **NAV** | [F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt |
| **EKRAR** | Sapim |
| **DÄCK** | Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless |
| **EXTRAFUNKTIONER** | tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide |

**Price: 65 000,00 kr**

## GEOMETRY

| RAM | S | M | L | XL |
|---|---|---|---|---|
| | LOW \| HIGH | LOW \| HIGH | LOW \| HIGH | LOW \| HIGH |
| Längd sadelrör (mm) | 400 | 420 | 465 | 495 |
| Vinkel sadelrör | 75,0° \| 75,5° | 75,1° \| 75,5° | 75,1° \| 75,6° | 75,1° \| 75,6° |
| Topprörets längd (mm) | 577 \| 575 | 603 \| 602 | 625 \| 624 | 653 \| 651 |
| Styrhuvud Längd (mm) | 90 | 95 | 105 | 115 |
| Vinkel styrhuvud | 66,0° \| 66,5° | 66,1° \| 66,5° | 66,1° \| 66,6° | 66,1° \| 66,6° |
| Gaffelvinkel (mm) | 44 | 44 | 44 | 44 |
| Spår (mm) | 119,5 \| 115,7 | 119,3 \| 115,6 | 119,2 \| 115,5 | 119 \| 115,4 |
| Hjulbas (mm) | 1145 \| 1144 | 1172 \| 1171 | 1196 \| 1195 | 1225 \| 1224 |
| Kedjestagslängd (mm) | 437 \| 435 | 437 \| 435 | 437 \| 435 | 437 \| 435 |
| Nedre fäste Drop (mm) | 48 \| 42 | 48 \| 42 | 48 \| 42 | 48 \| 42 |
| Stack (mm) | 606 \| 602 | 611 \| 607 | 620 \| 616 | 629 \| 625 |
| Reach (mm) | 415 \| 420 | 440 \| 445 | 460 \| 465 | 485 \| 490 |
| Stå över höjden (mm) | 774 \| 780 | 770 \| 776 | 762 \| 769 | 757 \| 764 |
| Styrets bredd (mm) | 780 | 780 | 780 | 780 |
| Stamlängd (mm) | 50 | 50 | 60 | 70 |
| Vevlängd (mm) | 170 | 170 | 175 | 175 |

*All specifications listed are subject to change without notice.*