



SPECS

RAM	
STORLEKAR	S/M, M/L, L/XL
FÄRGER	Black Lava/Mercury/Chrome
RAM	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
GAFFEL	Fox 40 Factory, GRIP X2 damper, 203mm, 20x110
BAKDÄMPARE	Fox DHX2 Factory, SLS coil, 225/75, custom tuned for Giant S/M:425#, M/L:450#, L/XL:475#
KOMPONENTER	
STYRE	Giant Contact SL TR35, 800x35mm, 20mm rise
GREPPAR	Giant Tactal Pro Single
STAM	TruVativ Descendant Direct Mount 35 S/M:50mm, M/L:50mm, L/XL:50mm
SADELSTOLPE	Giant Contact, 30.9mm, 0 offset, 400mm
SADEL	Giant Romero
DRIVLINÄ	
VÄXLAR	SRAM GX Eagle DH, 1x7
FRAMVÄXEL	N/A
BAKVÄXEL	SRAM GX Eagle DH
BROMSAR	Shimano Saint M-820, hydraulic, Shimano RT-66 rotors [F]220mm, [R]203mm
BROMSSPAKAR	Shimano Saint BL-M820
KASSETT	SRAM GX DH, 11-25
KEDJA	SRAM PC 1110
VEVPARTI	TruVativ Descendent DH, 34t, 56.5mm chainline S/M:165mm, M/L:170mm, L/XL:170mm
BROMSREGLAGE	SRAM DUB, threaded, 83mm

HJUL	
FÄLGAR	Giant TRA 2 rims, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
EKRAR	Stainless steel
DÄCK	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
EXTRAFUNKTIONER	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full down tube protector

Price: 96 990,00 kr

GEOMETRY

RAM	M/L			L/XL		
	LOW	MID	HIGH	LOW	MID	HIGH
Längd sadelrör (mm)	450			450		
Seat Post Insertion Depth (mm)	165			165		
Vinkel sadelrör	78,4° 78,8° 79,1°			78,5° 78,8° 79,1°		
Topprörets längd (mm)	591,3 590,5 589,8			611,3 610,6 609,8		
Styrhuvud Längd (mm)	110			110		
Vinkel styrhuvud	61,6° 62,0° 62,3°			61,7° 62,0° 62,3°		
Gaffelvinkel (mm)	52			52		
Spår (mm)	146,2 143,5 140,8			146 143,3 140,8		
Hjulbas (mm)	1293 1291,8 1290,6			1313 1311,9 1310,6		
Kedjestagslängd (mm)	447,9 446,5 445			447,9 446,5 445		
Nedre fäste Drop (mm)	13,3 8,3 3,1			13,5 8,4 3,2		
Stack (mm)	634,9 632,2 629,2			635,3 632,4 629,3		
Reach (mm)	461,2 464,9 468,6			481,5 485,1 488,6		
Stå över höjden (mm)	735,2 740 744,8			742,9 747,6 752,3		
Styrets bredd (mm)	800			800		
Stamlängd (mm)	50			50		
Vevlängd (mm)	165			165		
Hjulstorlek	[R] 27.5" / [F] 29"			[R] 27.5" / [F] 29"		

All specifications listed are subject to change without notice.