

REIGN ADVANCED E+ 2

GIANT



SPECS

HYBRID CYKELTEKNIK	
MOTOR	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
KONTROLLER	Giant RideControl Ergo 4
VISA	Giant RideControl GO Lux
BATTERI	Giant EnergyPak Smart 560Wh, integrated, 48V
LADDARE	Giant EnergyPak smart charger 4A, 48V
CONNECTIVITY	Aegis Tire Checker included in RideControl display
RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Moon Dust
RAM	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
GAFFEL	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
BAKDÄMPARE	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
KOMPONENTER	
STYRE	Giant Contact SL TR35, 35x800mm, 35mm rize, Up: 5° Back: 9°
GREPPAR	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
STAM	Giant Contact SL 35
SADELSTOLPE	Giant Contact Switch adjustable dropper, 30,9mm (S:110-140, M:140-170,L/XL: 170-200) MMX remote
SADEL	Giant Romero, Neutral
DRIVLINJA	
VÄXLAR	Shimano Deore
BAKVÄXEL	Shimano Deore, 12-speed shadow+
BROMSAR	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
BROMSSPAKAR	Shimano SLX
KASSETT	Shimano Deore, 10-51T, 12-speed
KEDJA	Shimano Deore 12-speed
VEVPARTI	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

HJUL	
FÄLGAR	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
NAV	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
EKRAR	Sapim Race [F] E-Lite [R], e-bike optimized
DÄCK	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
EXTRAFUNKTIONER	Aegis Tire Checker
TILLBEHÖR	
BELYSNING	Optional: - Giant Recon series e-bike lights available and direct connectable

Price: 80 990,00 kr

GEOMETRY

RAM	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Längd sadelrör (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	235			260			285			310		
Vinkel sadelrör	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°	77,5°	
Topprörets längd (mm)	570	569	568	602	601	600	625	624	623	657	656	655
Styrhuvud Längd (mm)	95			105			120			135		
Vinkel styrhuvud	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°	63,5°	
Gaffelvinkel (mm)	44			44			44			44		
Spår (mm)	133,3	130,3	127,4	133,3	130,3	127,4	133,3	130,3	127,4	133,3	130,3	
Hjulbas (mm)	1226	1226	1227	1261	1261	1261	1287	1288	1288	1323	1323	
Kedjestagslängd (mm)	450	450	450	450	450	450	450	450	450	450	450	450
Nedre fäste Drop (mm)	10	5		10	5		10	5		10	5	
Stack (mm)	647	645	642	656	654	651	669	667	665	683	680	678
Reach (mm)	426	430	435	456	460	465	476	480	485	505	510	515
Styrets bredd (mm)	800			800			800			800		
Stamlängd (mm)	40			40			40			40		
Vevlängd (mm)	160			160			160			160		
Hjulstorlek	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5" / F29"		

All specifications listed are subject to change without notice.