

REVOLT X ADVANCED PRO 0



SPECS

| FRAME | |
|-------------------------|---|
| SIZES | XS, S, M, M/L, L, XL |
| COLOURS | Kelp Forest/Charcoal/Chrome |
| FRAME | Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout |
| FORK | Fox 32 Float TC Performance Elite, 40mm, Fit 4 damper/12x100mm thru-axle |
| SHOCK | N/A |
| COMPONENTS | |
| HANDLEBAR | Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm |
| GRIPS | Stratus Lite 3.0 |
| STEM | Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm |
| SEATPOST | Post Moderne, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop |
| SADDLE | Giant Approach SL |
| PEDALS | N/A |
| DRIVETRAIN | |
| SHIFTERS | SRAM Force eTap AXS, 1x12 |
| FRONT DERAILLEUR | N/A |
| REAR DERAILLEUR | SRAM X01 Eagle AXS |
| BRAKES | SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm |
| BRAKE LEVERS | SRAM Force eTap AXS hydraulic |
| CASSETTE | SRAM XG-1295, 12-speed, 10x52 |
| CHAIN | SRAM X01 Eagle |
| CRANKSET | SRAM FORCE 1 Wide, DUB 1x 40T XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| BOTTOM BRACKET | SRAM DUB, press fit |

| WHEELS | |
|---------------|--|
| RIMS | Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm |
| HUBS | [F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle |
| SPOKES | Sapim Laser |
| TIRES | Maxxis Rambler, 700x50c, tubeless prepared |
| EXTRAS | tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position |

Suggested Retail Price (CDN): \$8,699.00

FRAME GEOMETRY

| FRAME | XS | S | M | M/L | L | XL |
|--------------------------|--------------------|-------------------------|-------------------------|-------------------------|----------------------|---------------|
| | SHORT LONG SHORT | LONG SHORT LONG SHORT | LONG SHORT LONG SHORT | LONG SHORT LONG SHORT | LONG SHORT LONG SH | LONG SH |
| Seat Tube Length (mm) | 430 | 450 | 470 | 490 | 510 | 530 |
| Seat Tube Angle | 74.0° 73.9° | 73.5° 73.4° | 73.5° 73.4° | 73.0° 72.9° | 73.0° 72.9° | 73.0° 72.9° |
| Top Tube Length (mm) | 543 | 553 | 560 | 575 | 585 | 600 |
| Head Tube Length (mm) | 90 | 100 | 115 | 130 | 145 | 160 |
| Head Tube Angle | 70.5° 70.4° | 71.0° 70.9° | 71.5° 71.4° | 72.0° 71.9° | 72.0° 71.9° | 72.0° 71.9° |
| Fork Rake (mm) | 50 | 50 | 50 | 50 | 50 | 50 |
| Trail (mm) | 80.3 83.7 | 76.9 80.3 | 73.5 76.8 | 70.1 73.4 | 70.1 73.4 | 70.1 73.4 |
| Wheelbase (mm) | 1023 1033 | 1024 1034 | 1026 1036 | 1031 1041 | 1041 1051 | 1051 1061 |
| Chain Stay Length (mm) | 425 435 | 425 435 | 425 435 | 425 435 | 425 435 | 425 435 |
| Bottom Bracket Drop (mm) | 68 69 | 68 69 | 68 69 | 68 69 | 68 69 | 68 69 |
| Stack (mm) | 549 | 560 | 576 | 592 | 607 | 622 |
| Reach (mm) | 386 | 387 | 389 | 393 | 399 | 410 |
| Stand Over Height (mm) | 720 726 | 736 743 | 755 761 | 772 778 | 790 796 | 800 806 |
| Handlebar Width (mm) | 440 | 440 | 460 | 460 | 480 | 480 |
| Stem Length (mm) | 50 | 60 | 70 | 80 | 80 | 90 |
| Crank Length (mm) | 170 | 170 | 172.5 | 172.5 | 175 | 175 |
| Wheel Size | 700x 42C | 700x 42C | 700x 42C | 700x 42C | 700x 42C | 700x 42C |

All prices and specifications are subject to change without notice.