



스펙

프레임	
사이즈	XS, S, M, M/L
색상	Pyrite Brown
프레임	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
포크	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
서스펜션	N/A
부품	
핸들바	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm
GRIPS	cork tape with gel
스텝	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm
시트포스트	Giant D-Fuse, alloy, 14mm offset
안장	Giant Approach
페달	N/A
구동계	
변속기	Shimano GRX RX-610, 2x12
앞 변속기	Shimano GRX RX-820
뒷 변속기	Shimano GRX RX-820
브레이크	Shimano GRX RX-410 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
브레이크 레버	Shimano GRX RX-610 hydraulic
스프라켓	Shimano 105, 11x34
체인	KMC X12L-1
크랭크 셋	FSA Omega Modular AGX+, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm
BB	FSA Mega EXO

바퀴	
휠	Giant S-X2 Disc wheelset, alloy
허브	Giant alloy, 12mm thru-axle
스포크	stainless
타이어	Maxxis Rambler/Ravager, 700x40c, tubeless
추가 기능	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

가격: ₩2,330,000

지오메트리

프레임	XS	S	M	ML
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
시트 튜브 길이 (mm)	430	450	470	490
시트 튜브 각도	74.0°	73.5°	73.5°	73.0°
탐튜브 길이 (mm)	540	550	560	575
헤드 튜브 길이 (mm)	125	135	150	165
헤드 튜브 각도	70.0°	71.0°	71.5°	72.0°
포크 레이크 (mm)	50	50	50	50
트레일 (mm)	78 82	72 75	68 72	65 68
휠베이스 (mm)	1029 1039	1025 1035	1030 1040	1035 1045
체인스테이 길이 (mm)	430 440	430 440	430 440	430 440
BB (mm)	80 81	80 81	80 81	80 81
스택 (mm)	556	570	586	602
범위 (mm)	381	381	387	391
스탠드 오버 (mm)	717 724	734 741	752 759	769 776
핸들바 폭 (mm)	420	420	440	440
스텝 길이 (mm)	50	60	70	80
크랭크 길이 (mm)	170	170	172.5	172.5
휠사이즈	700x 42C	700x 42C	700x 42C	700x 42C

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.