

리볼트 어드밴스 1

GIANT



스펙

프레임	
사이즈	XS, S, M, M/L, L, XL
색상	Ocean Twilight / Steampunk
프레임	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
포크	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
부품	
핸들바	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
스템	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
시트포스트	Post Moderne, dropper, 30.9mm, 30mm suspension XS:365mm, S:415mm, M:415mm, M/L:415mm, L:415mm, XL:415mm
안장	Giant Grit
구동계	
변속기	SRAM Apex 1, 1x12
뒷 변속기	SRAM Apex XPLR
브레이크	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]160mm
브레이크 레버	SRAM Rival 1, left lever dropper switch
스프라켓	SRAM PG-1231, 12-speed, 11x44
체인	SRAM Apex D1
크랭크 셋	SRAM Apex 1 Wide DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BB	SRAM DUB, press fit

바퀴	
휠	Giant P-X2 Disc wheelset, alloy
허브	Giant alloy, 12mm thru-axle
스포크	Sapim
타이어	Giant Crosscut Grip, 700x45c, tubeless
추가 기능	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
최대 타이어 클리어런스	53mm

가격: ₩3,310,000

지오메트리

프레임	XS		S		M		ML	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
시트 튜브 길이 (mm)	430	450	430	450	470	490	490	490
시트 튜브 각도	74.0°	73.5°	73.5°	73.5°	73.5°	73.0°	73.0°	73.0°
탐튜브 길이 (mm)	540	550	550	560	560	575	575	575
헤드 튜브 길이 (mm)	125	135	135	150	150	165	165	165
헤드 튜브 각도	70.0°	71.0°	71.0°	71.5°	71.5°	72.0°	72.0°	72.0°
포크 레이크 (mm)	50	50	50	50	50	50	50	50
트레일 (mm)	78 82	72 75	68 72	65 68	65 68	65 68	65 68	65 68
휠베이스 (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1031 1041	1031 1041	1031 1041	1031 1041
체인스테이 길이 (mm)	425 435	425 435	425 435	425 435	425 435	425 435	425 435	425 435
BB (mm)	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81
스택 (mm)	556	570	586	602	602	602	602	602
범위 (mm)	381	381	387	391	391	391	391	391
스탠드 오버 (mm)	724 731	740 747	757 764	774 780	774 780	774 780	774 780	774 780
핸들바 폭 (mm)	420	420	440	440	440	440	440	440
스템 길이 (mm)	50	60	70	80	80	80	80	80
크랭크 길이 (mm)	170	170	172.5	172.5	172.5	172.5	172.5	172.5
휠사이즈	700c	700c	700c	700c	700c	700c	700c	700c

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.