

레인 어드밴스 2

GIANT



스펙

프레임	
사이즈	S, M, L, XL
색상	Dried Matcha
프레임	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
포크	Fox 38 Rhythm, 170mm, GRIP damper, 15x110 Kabolt X, 44mm offset
서스펜션	Fox Float Performance, 205/62.5, custom tuned for Giant
부품	
핸들바	Giant Contact TR35, 800x35mm, 35mm rise
GRIPS	Giant Tactal Pro Single
스템	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
시트포스트	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
안장	Giant Romero SL
페달	
구동계	
변속기	Shimano SLX SL-M7100, 1x12
앞 변속기	N/A
뒷 변속기	Shimano SLX RD-M7100
브레이크	Shimano BR-MT520, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
브레이크 레버	Shimano Deore BL-MT501
스프라켓	Shimano Deore M6100, 10x51
체인	Shimano
크랭크 셋	Shimano SLX, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BB	Shimano, press fit

바퀴	
립	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
허브	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, MicroSpline driver body
스포크	Sapim, 28, straight pull, DBL Technology
타이어	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
추가 기능	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

가격: ₩5,690,000

지오메트리

프레임	S			M		
	LOW	MID	HIGH	LOW	MID	HIGH
시트 튜브 길이 (mm)	400			425		
Seat Post Insertion Depth (mm)	262			287		
시트 튜브 각도	77.5° 77.8° 78.2°			77.5° 77.8° 78.2°		
탐튜브 길이 (mm)	558 557 556			589 588 587		
헤드 튜브 길이 (mm)	100			105		
헤드 튜브 각도	62.7° 63.0° 63.4°			62.7° 63.0° 63.4°		
포크 레이크 (mm)	44			44		
트레일 (mm)	147 144 141			147 144 141		
휠베이스 (mm)	1214 1213 1212			1246 1245 1244		
체인스테이 길이 (mm)	445 443 442			445 443 442		
BB (mm)	29 24 19			29 24 19		
스택 (mm)	633 630 627			638 635 632		
범위 (mm)	418 421 426			448 452 456		
스탠드 오버 (mm)	714 718 723			733 738 742		
핸들바 폭 (mm)	800			800		
스템 길이 (mm)	40			40		
크랭크 길이 (mm)	165			170		
휠사이즈	29" [F] 27.5" [R]			29" [F] 27.5" [R]		

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.