



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Raw Carbon/Brushed Chrome
RAHMEN	Advanced Vollcarbon Rahmen, FlexPoint PRO Carbon Hinterbau, 100 mm Federweg, 12x148 mm
GABEL	Fox 34 Float SC Performance Elite Remote, 110mm, GRIP SL damper, Boost 15x110 Kabolt, 44mm Offset
DÄMPFER	Fox Float SL Performance Elite, three-position remote, 165/45, custom tuned for Giant
KOMPONENTEN	
LENKER	Giant Contact SLR XC Flat, Carbon, 760x35mm
GRIFFE	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
VORBAU	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
SATTELSTÜTZE	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm
SATTEL	Giant Grit SL
ANTRIEB	
SCHALTHEBEL	SRAM AXS Pod, discrete clamp, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM GX Eagle Transmission
BREMSEN	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-64 rotors [F]180mm, [R]160mm
BREMSHEBEL	Shimano Deore XT BL-M8100
KASSETTE	SRAM GX Eagle Transmission, 10x52
KETTE	SRAM GX Eagle Transmission
KURBEL	SRAM XO Eagle Transmission with power meter, 32t, 55mm chainline S:170mm, M:175mm, L:175mm, XL:175mm
TRETLAGER	SRAM DUB, press fit

LAUFRÄDER	
FELGEN	Giant XCR 1 30 Carbon WheelSystem, 30mm inner width
NABE	[F] Giant XC alloy, CenterLock, [R] Giant XC alloy, DT350 54t ratchet driver, CenterLock
SPEICHEN	Sapim Laser
REIFEN	Maxxis Aspen 29x2.4, foldable, 120tpi, TLR, EXO, tubeless
EXTRAS	Auslieferung als Tubeless-Version, max. Reifenfreiheit: 2.4", max. Kettenblattgröße: 34 Zähne

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	390	420	465	495
Seat Post Insertion Depth (mm)	185	225	260	290
Sitzrohrwinkel	75.5°	75.5°	75.5°	75.5°
Oberrohrlänge (mm)	572	604	626	653
Steuerrohr-Länge (mm)	90	95	105	115
Steuerrohr-Winkel	67.5°	67.5°	67.5°	67.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	109	109	109	109
Radstand (mm)	1127	1159	1183	1212
Kettenstreben-Länge (mm)	435	435	435	435
Tretlager-Höhe (mm)	42	42	42	42
Stack (mm)	589	593	603	612
Reach (mm)	420	450	470	495
Überstandshöhe (mm)	745	750	777	800
Lenkerbreite (mm)	760	760	760	760
Vorbaulänge (mm)	60	70	70	70
Kurbellänge (mm)	170	175	175	175
Radgröße	29"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.