

ANTHEM ADVANCED 29 1



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Raw Carbon/Brushed Chrome
FRAME	Advanced-Grade Composite front and rear triangles, 100mm FlexPoint Pro suspension, UDH hanger, 12x148mm thru-axle, 55mm Chainline
FORK	Fox 34 Float SC Performance Elite remote, 110mm, GRIP SL damper, Boost 15x110 Kabolt, 44mm offset
SHOCK	Fox Float SL Performance Elite, 3 position lockout, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SLR XC Flat, composite, 35mm
GRIPS	Giant XC Pro
STEM	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Grit SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, discrete clamp, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle T-Type AXS
BRAKES	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-64 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano Deore XT BL-M8100
CASSETTE	SRAM GX, T-Type 10x52
CHAIN	SRAM GX T-Type
CRANKSET	SRAM XO T-Type, Powermeter 32t, 55mm chainline S:170mm, M:175mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant XCR 1 30 Carbon WheelSystem, 30mm inner width
HUBS	[F] Giant XC alloy, CenterLock, [R] Giant XC alloy, DT350 54t ratchet driver, CenterLock
SPOKES	Sapim Laser
TYRES	Maxxis Aspen 29x2.4, foldable, TLR, EXO, tubeless
EXTRAS	Tubeless prepared, 2.4" max tyre size, 34t max chainring size, Giant/MRP CS chain guide

Price: \$9,499.00

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	390	420	465	495
Seat Post Insertion Depth (mm)	185	225	260	290
Seat Tube Angle	75.5°	75.5°	75.5°	75.5°
Top Tube Length (mm)	572	604	626	653
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	67.5°	67.5°	67.5°	67.5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	109	109	109	109
Wheelbase (mm)	1127	1159	1183	1212
Chain Stay Length (mm)	435	435	435	435
Bottom Bracket Drop (mm)	42	42	42	42
Stack (mm)	589	593	603	612
Reach (mm)	420	450	470	495
Stand Over Height (mm)	745	750	777	800
Stem Length (mm)	60	70	70	70
Crank Length (mm)	170	175	175	175
Wheel Size	29"	29"	29"	29"

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.