

ANTHEM ADVANCED 29 1

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Raw Carbon/Brushed Chrome
CUADRO	Advanced-grade composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
TIJERA	Fox 34 Float SC Performance Elite remote, 110mm, GRIP SL damper, Boost 15x110 Kabolt, 44mm offset
AMORTIGUADOR	Fox Float SL Performance Elite, three-position remote, 165/45, custom tuned for Giant
COMPONENTES	
MANUBRIO	Giant Contact SLR XC Flat, composite, 760x35mm
GRIPS	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
POTENCIA	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
POSTE DE ASIENTO	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm
ASIENTO	Giant Grit SL
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS Pod, discrete clamp, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	SRAM GX Eagle Transmission
FRENOS	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-64 rotors [F]180mm, [R]160mm
PALANCAS DE FRENOS	Shimano Deore XT BL-M8100
CASSETTE	SRAM GX Eagle Transmission, 10x52
CADENA	SRAM GX Eagle Transmission
MULTIPLICACIÓN	SRAM XO Eagle Transmission with power meter, 32t, 55mm chainline S:170mm, M:175mm, L:175mm, XL:175mm
EJE DE CENTRO	SRAM DUB, press fit

RUEDAS	
RUEDAS	Giant XCR 1 30 Carbon WheelSystem, 30mm inner width
MAZAS	[F] Giant XC alloy, CenterLock, [R] Giant XC alloy, DT350 54t ratchet driver, CenterLock
RAYOS	Sapim Laser
NEUMÁTICOS	Maxxis Aspen 29x2.4, foldable, 120tpi, TLR, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide

Precio: \$143,990.00

GEOMETRÍA

CUADRO	S	M	L	XL
Longitud de la Base del Poste de Asiento (mm)	390	420	465	495
Seat Post Insertion Depth (mm)	185	225	260	290
Ángulo de la Base del Poste de Asiento	75.5°	75.5°	75.5°	75.5°
Longitud del Tubo Superior (mm)	572	604	626	653
Longitud del Telescopio (mm)	90	95	105	115
Ángulo del Telescopio	67.5°	67.5°	67.5°	67.5°
Rake (mm)	44	44	44	44
Trail (mm)	109	109	109	109
Distancia entre Ejes (mm)	1127	1159	1183	1212
Longitud de Vaina Inferior (mm)	435	435	435	435
Caída del Eje de Centro (mm)	42	42	42	42
Stack (mm)	589	593	603	612
Reach (mm)	420	450	470	495
Altura del Tubo Superior al Suelo (mm)	745	750	777	800
Ancho del Manubrio (mm)	760	760	760	760
Longitud de la Potencia (mm)	60	70	70	70
Longitud de la Biela (mm)	170	175	175	175
Tamaño de las Ruedas	29"	29"	29"	29"

Todas las especificaciones están sujetas a cambios sin previo aviso.