

# ANTHEM ADVANCED 29 1

**GIANT**



## SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Dark Iridescent
FRAME	Advanced-grade composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
VOORVORK	Fox 34 Float SC Performance Elite remote, 110mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
DEMPER	Fox Float SL Performance Elite, three-position remote, 165/45, custom tuned for Giant
ONDERDELEN	
STUUR	Giant Contact SLR XC Flat, composite, 760x35mm
HANDVATTEN	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
STUURPEN	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
ZADELPEN	Giant Contact Switch Adjustable dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm
ZADEL	Fizik Antares R5 with Kium rails
PEDALEN	platform [GC,GT]
AFMONTAGE	
SHIFTERS	SRAM AXS Pod, discrete clamp, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	SRAM GX Eagle Transmission
REMMEN	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-64 rotors [F]180mm, [R]160mm
REMHENDELS	Shimano Deore XT BL-M8100
CASSETTE	SRAM GX Eagle Transmission, 10x52
AANDRIJVING	SRAM GX Eagle Transmission
CRANKSET	SRAM XO Eagle Transmission with power meter, 32t, 55mm chainline S:170mm, M:175mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant XCR 1 30 Carbon WheelSystem, 30mm inner width
NAVEN	[F] Giant XC alloy, CenterLock, [R] Giant XC alloy, DT350 54t ratchet driver, CenterLock
SPAKEN	Sapim Laser
BANDEN	Maxxis Aspen 29x2.4, foldable, 120tpi, TLR, EXO, tubeless
EXTRA'S	tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide

Adviesprijs: € 7.999,00

## GEOMETRIE

FRAME	S	M	L	XL
Zitbuis Lengte (mm)	390	420	465	495
Seat Post Insertion Depth (mm)	185	225	260	290
Zitbuis Hoek	75,5°	75,5°	75,5°	75,5°
Frame Lengte (horizontaal) (mm)	572	604	626	653
Balhoofdbuis Lengte (mm)	90	95	105	115
Balhoofdbuis Hoek	67,5°	67,5°	67,5°	67,5°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	109	109	109	109
Wielbasis (mm)	1127	1159	1183	1212
Liggende achtervork lengte (mm)	435	435	435	435
Bottom Bracket Drop (mm)	42	42	42	42
Stack (mm)	589	593	603	612
Reach (mm)	420	450	470	495
Stand Over Height (mm)	745	750	777	800
Stuur breedte (mm)	760	760	760	760
Stuurpen Lengte (mm)	60	70	70	70
Cranklengte (mm)	170	175	175	175
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.