

# ANTHEM ADVANCED 29 1

GIANT



## SPECS

QUADRO	
TAMANHOS	S, M, L, XL
CORES	Dark Iridescent
QUADRO	Advanced-grade composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
FORQUILHA	Fox 34 Float SC Performance Elite remote, 110mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
AMORTECEDORES	Fox Float SL Performance Elite, three-position remote, 165/45, custom tuned for Giant
COMPONENTES	
GUIADOR	Giant Contact SLR XC Flat, composite, 760x35mm
PUNHOS	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
AVANÇO	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
ESPIGÃO DE SELIM	Giant Contact Switch Adjustable dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm
SELIM	Fizik Antares R5 with Kium rails
PEDAIS	platform [GC,GT]
TRANSMISSÃO	
MANETES	SRAM AXS Pod, discrete clamp, 1x12
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	SRAM GX Eagle Transmission
TRAVÕES	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-64 rotors [F]180mm, [R]160mm
MANÍPULOS DOS TRAVÕES	Shimano Deore XT BL-M8100
CASSETTE	SRAM GX Eagle Transmission, 10x52
CORRENTE	SRAM GX Eagle Transmission
CONJUNTO PEDALEIRO	SRAM XO Eagle Transmission with power meter, 32t, 55mm chainline S:170mm, M:175mm, L:175mm, XL:175mm
MOVIMENTO CENTRAL	SRAM DUB, press fit

RODAS	
AROS	Giant XCR 1 30 Carbon WheelSystem, 30mm inner width
CUBOS	[F] Giant XC alloy, CenterLock, [R] Giant XC alloy, DT350 54t ratchet driver, CenterLock
RAIOS	Sapim Laser
PNEUS	Maxxis Aspen 29x2.4, foldable, 120tpi, TLR, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide

Preço: 6 999,00 €

## GEOMETRIA

QUADRO	S	M	L	XL
Comprimento do tubo do assento (mm)	390	420	465	495
Seat Post Insertion Depth (mm)	185	225	260	290
Ângulo do tubo do assento	75,5°	75,5°	75,5°	75,5°
Comprimento do tubo superior (mm)	572	604	626	653
Comprimento do tubo principal (mm)	90	95	105	115
Ângulo do tubo principal	67,5°	67,5°	67,5°	67,5°
Garfo ancinho (mm)	44	44	44	44
Trilha (mm)	109	109	109	109
distância entre eixos (mm)	1127	1159	1183	1212
Comprimento Chain Stay (mm)	435	435	435	435
Suporte inferior (mm)	42	42	42	42
Pilha (mm)	589	593	603	612
Alcancçar (mm)	420	450	470	495
Altura do standover (mm)	745	750	777	800
Largura do guidão (mm)	760	760	760	760
Comprimento da haste (mm)	60	70	70	70
Comprimento da Manivela (mm)	170	175	175	175
Tamanho da roda	29"	29"	29"	29"

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.