



## СПЕЦИФИКАЦИИ

| РАМКА                  |  |
|------------------------|--|
| РАЗМЕР                 | S, M, L, XL  |
| ЦВЯТ                   | Moonstone  |
| РАМКА                  | Advanced-grade composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle    |
| ВИЛКА                  | Fox 34 Float SC Performance Remote, 110mm, GRIP damper, Boost 15x110 Kabolt, 44mm offset, remote lockout |
| ЗАДЕН АМОРТИСЬОР       | Fox Float SL Performance Elite, three-position remote, 165/45, custom tuned for Giant                    |
| КОМПОНЕНТИ             |  |
| КОРМИЛО                | Giant Contact XC Flat, 760x35mm  |
| ГРИПОВЕ                | Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm   |
| ЛАПА                   | Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm  |
| КОЛЧЕ ЗА СЕДАЛКА       | Giant Contact Switch AT dropper 110-140mm travel / 30.9 x 395mm  |
| СЕДАЛКА                | Giant Grit SL  |
| ПЕДАЛИ                 |  |
| DRIVETRAIN             |  |
| КОМАНДИ                | Shimano Deore XT SL-M8100, 1x12  |
| ПРЕДЕН ДЕРАЙЛЪОР       | N/A  |
| ЗАДЕН ДЕРАЙЛЪОР        | Shimano Deore XT RD-M8100  |
| СПИРАЧКИ               | Shimano SLX BR-M7100, hydraulic, Shimano RT-56 rotors [F]180mm, [R]160mm                                 |
| РЪКОХВАТКИ ЗА СПИРАЧКИ | Shimano Deore BL-M7100   |
| КАСЕТА                 | Shimano Deore XT M8100, 10x51  |
| ВЕРИГА                 | KMC X-12   |
| КУРБЕЛ                 | Shimano Deore XT 8120, 32t, 55mm chainline S:170mm, M:175mm, L:175mm, XL:175mm                           |
| СРЕДНА КАСЕТА          | Shimano, press fit   |

| КАПЛИ   |   |
|---------|---|
| ШИНИ    | Giant XCR 2.29 Carbon WheelSystem   |
| ГЛАВИНИ | [F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt                 |
| СПИЦИ   | Sapim   |
| ГУМИ    | Maxxis Aspen 29x2.4, foldable, 120tpi, TLR, EXO, tubeless                               |
| ЕКСТРИ  | tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide |

## ГЕОМЕТРИЯ

| РАМКА                          | S     | M     | L     | XL    |
|--------------------------------|-------|-------|-------|-------|
| Seat Tube Length (mm)          | 390   | 420   | 465   | 495   |
| Seat Post Insertion Depth (mm) | 185   | 225   | 260   | 290   |
| Seat Tube Angle                | 75,5° | 75,5° | 75,5° | 75,5° |
| Top Tube Length (mm)           | 572   | 604   | 626   | 653   |
| Head Tube Length (mm)          | 90    | 95    | 105   | 115   |
| Head Tube Angle                | 67,5° | 67,5° | 67,5° | 67,5° |
| Fork Rake (mm)                 | 44    | 44    | 44    | 44    |
| Trail (mm)                     | 109   | 109   | 109   | 109   |
| Wheelbase (mm)                 | 1127  | 1159  | 1183  | 1212  |
| Chain Stay Length (mm)         | 435   | 435   | 435   | 435   |
| Bottom Bracket Drop (mm)       | 42    | 42    | 42    | 42    |
| Stack (mm)                     | 589   | 593   | 603   | 612   |
| Обсер (mm)                     | 420   | 450   | 470   | 495   |
| Stand Over Height (mm)         | 745   | 750   | 777   | 800   |
| Ширина на Кормило (mm)         | 760   | 760   | 760   | 760   |
| Дължина на Лапа (mm)           | 60    | 70    | 70    | 70    |
| Дължина на Курбел (mm)         | 170   | 175   | 175   | 175   |
| Размер на Каплите              | 29"   | 29"   | 29"   | 29"   |

All specifications listed are subject to change without notice.