

ANTHEM ADVANCED 29 2



產品規格

車架	
尺寸	S, M, L
顏色	Golden Haze/Chrome 薄霧金
車架	Advanced碳纖維前後三角, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
前叉	Fox 34 Float SC Performance Remote, 110mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, remote lockout,
避震器	Fox Float SL Performance Elite, three-position remote, 165/45,
COMPONENTS	
車把手	Giant Contact XC Flat, 760x35mm
把手帶/套	Giant XC Pro S:32mm, M:32mm, L:34mm,
豎桿	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm,
座桿	Giant Contact Switch Adjustable dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm
坐墊	Fi'zi:k Antares R7 with S-alloy rails
踏板	platform [GC,GT]
DRIVETRAIN	
變速把手	Shimano Deore XT SL-M8100, 1x12
前變速器	N/A
後變速器	Shimano Deore XT RD-M8100
煞車系統	Shimano SLX BR-M7100, hydraulic, Shimano RT-56 rotors [F]180mm, [R]160mm
煞車把手	Shimano Deore BL-M7100
飛輪	Shimano SLX M7100, 10x51
鍊條	KMC X-12
大齒盤	Shimano SLX, 32t, 55mm chainline S:170mm, M:175mm, L:175mm,
BOTTOM BRACKET (B B)	Shimano, press fit

輪組	
輪圈	Giant XCR 2 29 Carbon WheelSystem
花鼓	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
輻條	Sapim
外胎	Maxxis Aspen 29x2.4, foldable, 120tpi, TLR, EXO, tubeless
其他	tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide

Price: NT\$128,000

車架幾何

車架	S	M	L	XL
座(立)管長 (mm)	390	420	465	495
Seat Post Insertion Depth (mm)	185	225	260	290
座(立)管角度	75.5°	75.5°	75.5°	75.5°
上管長度 (mm)	572	604	626	653
頭管長度 (mm)	90	95	105	115
頭管角度	67.5°	67.5°	67.5°	67.5°
前叉 (mm)	44	44	44	44
Trail (mm)	109	109	109	109
前後輪距 (mm)	1127	1159	1183	1212
後下叉長度 (mm)	435	435	435	435
五通下降高度 (mm)	42	42	42	42
頭碗至五通高度 (mm)	589	593	603	612
頭碗至五通長度 (mm)	420	450	470	495
上管至地面高度 (mm)	745	750	777	800
把手寬 (mm)	760	760	760	760
龍頭長度 (mm)	60	70	70	70
曲柄長度 (mm)	170	175	175	175
輪組尺寸	29"	29"	29"	29"

* 捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。