

ANTHEM ADVANCED 29 3

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, L, XL
FARVER	Sea Sparkle
RAMME	Advanced-grade composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
FORGAFFEL	RockShox Sid, 110mm, Boost 15x110, 44mm offset, remote lockout, custom tuned for Giant
BAGDÆMPER	Fox Float SL Performance, 165/45, remote, custom tuned for Giant
KOMPONENTER	
STYR	Giant Contact XC Flat, 760x35mm
GREB / STYRBÅND	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
FREMPIND	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
SADELPIND	Giant Contact Switch Adjustable dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm
SADEL	Fi'ziik Antares R7 with S-alloy rails
PEDALER	platform [GC,GT]
GEARGRUPPE	
SKIFTEGREB	Shimano Deore SL-M6100, 1x12
FORSKIFTER	N/A
BAGSKIFTER	Shimano Deore RD-M6100
BREMSE	Shimano Deore MT410, hydraulic, Shimano RT-26 rotors [F]180mm, [R]160mm
BREMSEGREB	Shimano Deore MT401
KASSETTE	Shimano Deore M6100, 10x51
KÆDE	KMC X-12
KRANKSÆT	Praxis Cadet, 32t, 55mm chainline S:170mm, M:175mm, L:175mm, XL:175mm
KRANKBOKS	Shimano, press fit

HJUL	
FÆLGE	Giant XCR 2 29 Carbon WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
EGER	Sapim
DÆK	Maxxis Aspen 29x2.4, foldable, 120tpi, TLR, EXO, tubeless
EKSTRA	tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide

Pris: 36.499,00 kr.

GEOMETRI

RAMME	S	M	L	XL
Sadelrørslængde (mm)	390	420	465	495
Sadelpindindsætningsdybde (mm)	185	225	260	290
Sadelrørsvinkel	75,5°	75,5°	75,5°	75,5°
Overrørslængde (mm)	572	604	626	653
Kronrørslængde (mm)	90	95	105	115
Kronrørsvinkel	67,5°	67,5°	67,5°	67,5°
Forgaffel fremspring (rake) (mm)	44	44	44	44
Sti (mm)	109	109	109	109
Akselafstand (mm)	1127	1159	1183	1212
Kædestagslængde (mm)	435	435	435	435
Krankboks drop (mm)	42	42	42	42
Stack (mm)	589	593	603	612
Reach (mm)	420	450	470	495
Skridthøjde (mm)	745	750	777	800
Styrbredde (mm)	760	760	760	760
Frempindslængde (mm)	60	70	70	70
Pedalarmslængde (mm)	170	175	175	175
Hjulstørrelse	29"	29"	29"	29"

Alle de anførte specifikationer kan ændres uden varsel.