

ANTHEM ADVANCED 29 3

GIANT



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, L, XL
VÄRIT	Sea Sparkle
RUNKO	Advanced-grade composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
HAARUKKA	RockShox Sid, 110mm, Boost 15x110, 44mm offset, remote lockout, custom tuned for Giant
ISKUNVAIMENNIN	Fox Float SL Performance, 165/45, remote, custom tuned for Giant
KOMONENTIT	
OHJAUSTANKO	Giant Contact XC Flat, 760x35mm
GRIPIT	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
OHJAINKANNATIN	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
SATULATOLPPA	Giant Contact Switch Adjustable dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm
SATULA	Fi'zi:k Antares R7 with S-alloy rails
POLKIMET	platform [GC,GT]
VOIMANSIIRTO	
VAIHDEVIPU	Shimano Deore SL-M6100, 1x12
ETUVAIHTAJA	N/A
TAKAVAIHTAJA	Shimano Deore RD-M6100
JARRUT	Shimano Deore MT410, hydraulic, Shimano RT-26 rotors [F]180mm, [R]160mm
JARRUKAHVAT	Shimano Deore MT401
RATASPAKKA	Shimano Deore M6100, 10x51
KETJUT	KMC X-12
KAMPISARJA	Praxis Cadet, 32t, 55mm chainline S:170mm, M:175mm, L:175mm, XL:175mm
KESKIÖ	Shimano, press fit

RENKAAT	
VANTEET	Giant XCR 2 29 Carbon WheelSystem
NAVAT	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
PINNAT	Sapim
RENKAAT	Maxxis Aspen 29x2.4, foldable, 120tpi, TLR, EXO, tubeless
LISÄTIEDOT	tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide

Suositus hinta: 4 869,00 €

GEOMETRIA

RUNKO	S	M
Satulaputken pituus (mm)	390	420
Satulatolpan asennussyvyys (mm)	185	225
Satulaputken kulma	75,5°	75,5°
Vaakaputken pituus (mm)	572	604
Emäputken pituus (mm)	90	95
Emäputken kulma	67,5°	67,5°
Haarukan offset (mm)	44	44
Trail-mitta (mm)	109	109
Akseliväli (mm)	1127	1159
Takahaarukan alaputken pituus (mm)	435	435
Keskiön pudotus (mm)	42	42
Stack-mitta (mm)	589	593
Reach-mitta (mm)	420	450
Standover-mitta (mm)	745	750
Ohjaustangon leveys (mm)	760	760
Ohjainkannattimen pituus (mm)	60	70
Kammen pituus (mm)	170	175
Rengaskoko	29"	29"

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.