

ANTHEM ADVANCED 29 3

GIANT



SPECIFICATIES

| FRAME | |
|------------------|---|
| MATEN | S, M, L, XL |
| KLEUREN | Sea Sparkle |
| FRAME | Advanced-grade composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle |
| VOORVORK | RockShox Sid, 110mm, Boost 15x110, 44mm offset, remote lockout, custom tuned for Giant |
| DEMPER | Fox Float SL Performance, 165/45, remote, custom tuned for Giant |
| ONDERDELEN | |
| STUUR | Giant Contact XC Flat, 760x35mm |
| HANDVATTEN | Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm |
| STUURPEN | Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm |
| ZADELPEN | Giant Contact Switch Adjustable dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm |
| ZADEL | Fi'zi:k Antares R7 with S-alloy rails |
| PEDALEN | platform [GC,GT] |
| AFMONTAGE | |
| SHIFTERS | Shimano Deore SL-M6100, 1x12 |
| VOORDERAILLEUR | N/A |
| ACHTERDERAILLEUR | Shimano Deore RD-M6100 |
| REMMEN | Shimano Deore MT410, hydraulic, Shimano RT-26 rotors [F]180mm, [R]160mm |
| REMHENDELS | Shimano Deore MT401 |
| CASSETTE | Shimano Deore M6100, 10x51 |
| AANDRIJVING | KMC X-12 |
| CRANKSET | Praxis Cadet, 32t, 55mm chainline S:170mm, M:175mm, L:175mm, XL:175mm |
| BOTTOM BRACKET | Shimano, press fit |

| WIELSET | |
|---------|---|
| VELGEN | Giant XCR 2 29 Carbon WheelSystem |
| NAVEN | [F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt |
| SPAKEN | Sapim |
| BANDEN | Maxxis Aspen 29x2.4, foldable, 120tpi, TLR, EXO, tubeless |
| EXTRA'S | tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide |

Adviesprijs: € 4.699,00

GEOMETRIE

| FRAME | S | M | L | XL |
|---------------------------------|-------|-------|-------|-------|
| Zitbuis lengte (mm) | 390 | 420 | 465 | 495 |
| Seat Post Insertion Depth (mm) | 185 | 225 | 260 | 290 |
| Zitbuis hoek | 75,5° | 75,5° | 75,5° | 75,5° |
| Frame Lengte (horizontaal) (mm) | 572 | 604 | 626 | 653 |
| Balhoofdbuis Lengte (mm) | 90 | 95 | 105 | 115 |
| Balhoofdbuis Hoek | 67,5° | 67,5° | 67,5° | 67,5° |
| Vork Sprong (mm) | 44 | 44 | 44 | 44 |
| Naloop (mm) | 109 | 109 | 109 | 109 |
| Wielbasis (mm) | 1127 | 1159 | 1183 | 1212 |
| Liggende achtervork lengte (mm) | 435 | 435 | 435 | 435 |
| Bottom Bracket Drop (mm) | 42 | 42 | 42 | 42 |
| Stack (mm) | 589 | 593 | 603 | 612 |
| Reach (mm) | 420 | 450 | 470 | 495 |
| Stand Over Height (mm) | 745 | 750 | 777 | 800 |
| Stuur breedte (mm) | 760 | 760 | 760 | 760 |
| Stuurpen Lengte (mm) | 60 | 70 | 70 | 70 |
| Cranklengte (mm) | 170 | 175 | 175 | 175 |
| Wielmaat | 29" | 29" | 29" | 29" |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.