



SPECS

| FRAME            |                                                                                                                                                                            |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SIZES            | S, M, L, XL                                                                                                                                                                |
| COLORS           | Raw Carbon / Chrome                                                                                                                                                        |
| FRAME            | Advanced-Grade Composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle                                                                      |
| FORK             | Fox 34 Float SC Factory Live Valve, 110mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant                                                           |
| SHOCK            | Fox Factory Live Valve, 165/45, custom tuned for Giant                                                                                                                     |
| COMPONENTS       |                                                                                                                                                                            |
| HANDLEBAR        | Giant Contact SLR XC Flat, composite, 760x35mm                                                                                                                             |
| GRIPS            | Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm                                                                                                                               |
| STEM             | Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm                                                                                                                  |
| SEATPOST         | Fox Transfer Factory, dropper, remote S: 125mm travel / 30.9 x 363.5mm M: 150mm travel / 30.9 x 418.3mm L: 150mm travel / 30.9 x 418.3mm XL: 175mm travel / 30.9 x 475.1mm |
| SADDLE           | Fi'zi:k Antares R5 with Kium rails                                                                                                                                         |
| PEDALS           | N/A                                                                                                                                                                        |
| DRIVETRAIN       |                                                                                                                                                                            |
| SHIFTERS         | SRAM XX Eagle AXS Rocker Paddle, 1x12                                                                                                                                      |
| FRONT DERAILLEUR | N/A                                                                                                                                                                        |
| REAR DERAILLEUR  | SRAM XX Eagle AXS                                                                                                                                                          |
| BRAKES           | Shimano XTR BR-MT9100, hydraulic, Shimano RT-64 rotors [F]180mm, [R]160mm                                                                                                  |
| BRAKE LEVERS     | Shimano XTR BL-M9100                                                                                                                                                       |
| CASSETTE         | SRAM XX Eagle, 10x52                                                                                                                                                       |
| CHAIN            | SRAM XX Eagle                                                                                                                                                              |
| CRANKSET         | SRAM XX Eagle, Quarq power meter, 32t S:170mm, M:175mm, L:175mm, XL:175mm                                                                                                  |
| BOTTOM BRACKET   | SRAM DUB, press fit                                                                                                                                                        |

| WHEELS |                                                                                         |
|--------|-----------------------------------------------------------------------------------------|
| RIMS   | DT Swiss XRC 1200 Spline 29                                                             |
| HUBS   | DT Swiss XRC 1200                                                                       |
| SPOKES | DT Swiss XRC 1200, straight pull                                                        |
| TIRES  | Maxxis Recon Race 29x2.4, foldable, TLR, EXO, tubeless                                  |
| EXTRAS | tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP SL chain guide |

GEOMETRY

| FRAME                    | S     | M     | L     | XL    |
|--------------------------|-------|-------|-------|-------|
| Seat Tube Length (mm)    | 390   | 420   | 465   | 495   |
| Seat Tube Angle          | 75,5° | 75,5° | 75,5° | 75,5° |
| Top Tube Length (mm)     | 572   | 604   | 626   | 653   |
| Head Tube Length (mm)    | 90    | 95    | 105   | 115   |
| Head Tube Angle          | 67,5° | 67,5° | 67,5° | 67,5° |
| Fork Rake (mm)           | 44    | 44    | 44    | 44    |
| Trail (mm)               | 109   | 109   | 109   | 109   |
| Wheelbase (mm)           | 1127  | 1159  | 1183  | 1212  |
| Chain Stay Length (mm)   | 435   | 435   | 435   | 435   |
| Bottom Bracket Drop (mm) | 42    | 42    | 42    | 42    |
| Stack (mm)               | 589   | 593   | 603   | 612   |
| Reach (mm)               | 420   | 450   | 470   | 495   |
| Stand Over Height (mm)   | 745   | 750   | 777   | 800   |
| Handlebar Width (mm)     | 760   | 760   | 760   | 760   |
| Stem Length (mm)         | 60    | 70    | 70    | 70    |
| Crank Length (mm)        | 170   | 175   | 175   | 175   |
| Wheel Size               | 29"   | 29"   | 29"   | 29"   |

All specifications listed are subject to change without notice.