



SPECS

CADRU	
MARIMI	S, M, L, XL
CULORI	Raw Carbon / Chrome
CADRU	Advanced-Grade Composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
FURCA	Fox 34 Float SC Factory Live Valve, 110mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
SOC	Fox Factory Live Valve, 165/45, custom tuned for Giant
COMPONENTE	
GHIDON	Giant Contact SLR XC Flat, composite, 760x35mm
GRIPS	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
PIPA	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
TIJA SA	Fox Transfer Factory, dropper, remote S: 125mm travel / 30.9 x 363.5mm M: 150mm travel / 30.9 x 418.3mm L: 150mm travel / 30.9 x 418.3mm XL: 175mm travel / 30.9 x 475.1mm
SA	Fi'zi:k Antares R5 with K:iium rails
PEDALE	N/A
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM XX Eagle AXS Rocker Paddle, 1x12
SCHIMBATOR FATA	N/A
SCHIMBATOR SPATE	SRAM XX Eagle AXS
FRANE	Shimano XTR BR-MT9100, hydraulic, Shimano RT-64 rotors [F]180mm, [R]160mm
MANETE FRANA	Shimano XTR BL-M9100
PINIOANE	SRAM XX Eagle, 10x52
LANT	SRAM XX Eagle
ANGRENAJ	SRAM XX Eagle, Quarq power meter, 32t S:170mm, M:175mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

ROTI	
JANTE	DT Swiss XRC 1200 Spline 29
BUTUCI	DT Swiss XRC 1200
SPITE	DT Swiss XRC 1200, straight pull
ANVELOPE	Maxxis Recon Race 29x2.4, foldable, TLR, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP SL chain guide

GEOMETRIE

CADRU	S	M	L	XL
Seat Tube Length (mm)	390	420	465	495
Seat Tube Angle	75,5°	75,5°	75,5°	75,5°
Top Tube Length (mm)	572	604	626	653
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	67,5°	67,5°	67,5°	67,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	109	109	109	109
Wheelbase (mm)	1127	1159	1183	1212
Chain Stay Length (mm)	435	435	435	435
Bottom Bracket Drop (mm)	42	42	42	42
Stack (mm)	589	593	603	612
Reach (mm)	420	450	470	495
Stand Over Height (mm)	745	750	777	800
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	60	70	70	70
Crank Length (mm)	170	175	175	175
Wheel Size	29"	29"	29"	29"

Toate specificatiile enumerate se pot schimba fara notificare prealabila.