

# ANTHEM ADVANCED PRO 29 1

**GIANT**



## SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Chameleon Saturn / Carbon
FRAME	Advanced-Grade Composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
VOORVORK	Fox 34 Float SC Performance Elite Live Valve, 110mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
DEMPER	Fox Performance Elite Live Valve, 165/45, custom tuned for Giant
ONDERDELEN	
STUUR	Giant Contact SLR XC Flat, composite, 760x35mm
HANDVATTEN	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
STUURPEN	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
ZADELPEN	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 440mm XL: 150mm travel / 30.9 x 445mm
ZADEL	Fi'zi:k Antares R5 with Kium rails
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	Shimano Deore XT SL-M8100, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	Shimano Deore XT RD-M8100
REMMEN	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-64 rotors [F]180mm, [R]160mm
REMHENDELS	Shimano Deore XT BL-M8100
CASSETTE	Shimano Deore XT M8100, 10x51
AANDRIJVING	KMC X-12
CRANKSET	Shimano Deore XT, 32t S:170mm, M:175mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant XCR 1 29 Carbon WheelSystem
NAVEN	Giant XCR 1 29 Carbon WheelSystem
SPAKEN	Giant XCR 1 29 Carbon WheelSystem
BANDEN	Maxxis Recon Race 29x2.4, foldable, TLR, EXO, tubeless
EXTRA'S	tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide

Adviesprijs: € 7.699,00

## GEOMETRIE

FRAME	S	M	L	XL
Zitbuis lengte (mm)	390	420	465	495
Zitbuis hoek	75,5°	75,5°	75,5°	75,5°
Frame Lengte (horizontaal) (mm)	572	604	626	653
Balhoofdbuis Lengte (mm)	90	95	105	115
Balhoofdbuis Hoek	67,5°	67,5°	67,5°	67,5°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	109	109	109	109
Wielbasis (mm)	1127	1159	1183	1212
Liggende achtervork lengte (mm)	435	435	435	435
Bottom Bracket Drop (mm)	42	42	42	42
Stack (mm)	589	593	603	612
Reach (mm)	420	450	470	495
Stand Over Height (mm)	745	750	777	800
Stuur breedte (mm)	760	760	760	760
Stuurpen Lengte (mm)	60	70	70	70
Cranklengte (mm)	170	175	175	175
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.