

# ANTHEM ADVANCED PRO 29 3

**GIANT**



## SPECS

FRAME	
<b>SIZES</b>	S, M, L, XL
<b>COLOURS</b>	Phoenix Fire/Carbon
<b>FRAME</b>	Advanced-Grade Composite front and rear triangles, 100mm FlexPoint Pro suspension, UDH hanger, 12x148mm thru-axle, 55mm Chainline
<b>FORK</b>	RockShox Sid, 110mm, Boost 15x110, 44mm offset, remote lockout, custom tuned for Giant
<b>SHOCK</b>	Fox Float DPS Performance, custom tuned for Giant
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact XC Flat, composite
<b>GRIPS</b>	Giant XC Pro
<b>STEM</b>	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
<b>SEATPOST</b>	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm, M: 125mm travel / 30.9 x 395mm, L: 150mm travel / 30.9 x 440mm, XL: 150mm travel / 30.9 x 440mm
<b>SADDLE</b>	Fi'zik Antares R7 with S-alloy rails
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Deore SL-M6100, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	Shimano Deore RD-M6100
<b>BRAKES</b>	Shimano Deore MT410, hydraulic, Shimano RT-26 rotors [F]180mm, [R]160mm
<b>BRAKE LEVERS</b>	Shimano Deore MT401
<b>CASSETTE</b>	Shimano Deore M6100, 10x51
<b>CHAIN</b>	KMC X-12
<b>CRANKSET</b>	Praxis Cadet, 32t, 55mm chainline
<b>BOTTOM BRACKET</b>	Praxis, press fit

WHEELS	
<b>RIMS</b>	Giant XCR 2 29 Carbon WheelSystem
<b>HUBS</b>	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
<b>SPOKES</b>	Sapim
<b>TIRES</b>	Maxxis Recon Race 29x2.4, foldable, TLR, EXO, tubeless
<b>EXTRAS</b>	Tubeless prepared, 2.4" max tyre size, 34t max chainring size, Giant/MRP CS chain guide

**Price: \$6,199.00**

## GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	390	420	465	495
Seat Tube Angle	75.5°	75.5°	75.5°	75.5°
Top Tube Length (mm)	572	604	626	653
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	67.5°	67.5°	67.5°	67.5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	109	109	109	109
Wheelbase (mm)	1127	1159	1183	1212
Chain Stay Length (mm)	435	435	435	435
Bottom Bracket Drop (mm)	42	42	42	42
Stack (mm)	489	593	603	612
Reach (mm)	420	450	470	495
Stand Over Height (mm)	745	750	777	800
Stem Length (mm)	60	70	70	70
Crank Length (mm)	170	175	175	175
Wheel Size	29"	29"	29"	29"

*Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.*