



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Phoenix Fire/Carbon
FRAME	Advanced-Grade Composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
FORK	RockShox Sid, 110mm, Boost 15x110, 44mm offset, remote lockout, custom tuned for Giant
SHOCK	Fox Float DPS Performance, 165/45, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact XC Flat, composite, 760x35mm
GRIPS	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
STEM	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
SEATPOST	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm
SADDLE	Fi'z'ik Antares R7 with S-alloy rails
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore SL-M6100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore RD-M6100
BRAKES	Shimano Deore MT410, hydraulic, Shimano RT-26 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano Deore MT401
CASSETTE	Shimano Deore M6100, 10x51
CHAIN	KMC X-12
CRANKSET	Praxis Cadet, 32t, 55mm chainline S:170mm, M:175mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant XCR 2 29 Carbon WheelSystem
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	Maxxis Recon Race 29x2.4, foldable, TLR, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	390	420	465	495
Seat Tube Angle	75,5°	75,5°	75,5°	75,5°
Top Tube Length (mm)	572	604	626	653
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	67,5°	67,5°	67,5°	67,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	109	109	109	109
Wheelbase (mm)	1127	1159	1183	1212
Chain Stay Length (mm)	435	435	435	435
Bottom Bracket Drop (mm)	42	42	42	42
Stack (mm)	489	593	603	612
Reach (mm)	420	450	470	495
Stand Over Height (mm)	745	750	777	800
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	60	70	70	70
Crank Length (mm)	170	175	175	175
Wheel Size	29"	29"	29"	29"

All specifications listed are subject to change without notice.