



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Phoenix Fire/Carbon
OKVIR	Advanced-Grade Composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
VILICE	RockShox Sid, 110mm, Boost 15x110, 44mm offset, remote lockout, custom tuned for Giant
AMORTIZER	Fox Float DPS Performance, 165/45, custom tuned for Giant
KOMPONENTE	
KRMILO	Giant Contact XC Flat, composite, 760x35mm
GRIPS	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
OPORA KRMILA	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
OPORA SEDEŽA	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm
SEDEŽ	Fi'zi:k Antares R7 with S-alloy rails
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	Shimano Deore SL-M6100, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano Deore RD-M6100
ZAVORE	Shimano Deore MT410, hydraulic, Shimano RT-26 rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	Shimano Deore MT401
VERIŽNIK	Shimano Deore M6100, 10x51
VERIGA	KMC X-12
GONILKE Z VERIŽNIKI	Praxis Cadet, 32t, 55mm chainline S:170mm, M:175mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant XCR 2 29 Carbon WheelSystem
PESTA	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
NAPERE	Sapim
PLAŠČI	Maxxis Recon Race 29x2.4, foldable, TLR, EXO, tubeless
DODATKI	tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide

GEOMETRIJA

OKVIR	S	M	L	XL
Dolžina sedežne cevi (mm)	390	420	465	495
Kot sedežne cevi	75,5°	75,5°	75,5°	75,5°
Top Tube Length (mm)	572	604	626	653
Višina glave okvirja (mm)	90	95	105	115
Krmilni kot	67,5°	67,5°	67,5°	67,5°
Zamik vpetja osi (mm)	44	44	44	44
Trail (mm)	109	109	109	109
Medosna razdalja (mm)	1127	1159	1183	1212
Dolžina cevi ob verigi (mm)	435	435	435	435
Bottom Bracket Drop (mm)	42	42	42	42
Oddaljenost zgornje cevi od gonilne osi (mm)	489	593	603	612
Doseg (mm)	420	450	470	495
Višina zgornje cevi (mm)	745	750	777	800
Širina krmila (mm)	760	760	760	760
Dolžina opore krmila (mm)	60	70	70	70
Dolžina gonilke (mm)	170	175	175	175
Velikost obročnikov	29"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.