



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	S, M, L, XL
ЦВЯТ	Gloss Raw Carbon/Matte Raw Carbon
РАМКА	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
ВИЛКА	RockShox Sid Ultimate 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
ЗАДЕН АМОРТИСЬОР	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
КОМПОНЕНТИ	
КОРМИЛО	Giant Integrated XC, composite, 780mm, 9-degree upsweep
ГРИПОВЕ	SRAM TwistLoc Ultimate
ЛАПА	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
КОЛЧЕ ЗА СЕДАЛКА	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel /
СЕДАЛКА	Giant Grit SL
ПЕДАЛИ	N/A
DRIVETRAIN	
КОМАНДИ	SRAM AXS Pod, 1x12
ПРЕДЕН ДЕРАЙЛЪОР	N/A
ЗАДЕН ДЕРАЙЛЪОР	SRAM XX SL Eagle Transmission
СПИРАЧКИ	SRAM Motive ULT, hydraulic, SRAM HS2 6-bolt rotors [F]180mm, [R]160mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	SRAM Motive ULT
КАСЕТА	SRAM XS 1297 Eagle Transmission, 10x52
ВЕРИГА	SRAM XX Eagle Transmission
КУРБЕЛ	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
СРЕДНА КАСЕТА	SRAM DUB, press fit

КАПЛИ	
ШИНИ	Giant XCR WheelSystem
ГЛАВИНИ	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
СПИЦИ	Carbon
ГУМИ	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
ЕКСТРИ	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

ГЕОМЕТРИЯ

РАМКА	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	420	465	495
Seat Tube Angle	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°
Top Tube Length (mm)	576 574	602 600	624 623	651 650
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2
Wheelbase (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Chain Stay Length (mm)	437 435	437 435	437 435	437 435
Bottom Bracket Drop (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Обсер (mm)	420 425	445 450	465 470	490 495
Stand Over Height (mm)	769 775	764 771	758 763	751 758
Ширина на Кормило (mm)	780	780	780	780
Дължина на Лапа (mm)	60	70	70	80
Дължина на Курбел (mm)	170	170	175	175

All specifications listed are subject to change without notice.