

ANTHEM ADVANCED SL 0

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, L, XL
FARVER	Gloss Raw Carbon/Matte Raw Carbon
RAMME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORGAFFEL	RockShox Sid Ultimate 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
BAGDÆMPER	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTER	
STYR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GREB / STYRBÅND	SRAM TwistLoc Ultimate
FREMPIND	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SADELPIND	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel /
SADEL	Giant Grit SL
PEDALER	N/A
GEARGRUPPE	
SKIFTEGREB	SRAM AXS Pod, 1x12
FORSKIFTER	N/A
BAGSKIFTER	SRAM XX Eagle Transmission
BREMSEER	SRAM Motive ULT, hydraulic, SRAM HS2 6-bolt rotors [F]180mm, [R]160mm
BREMSEGREB	SRAM Motive ULT
KASSETTE	SRAM XS 1297 Eagle Transmission, 10x52
KÆDE	SRAM XX Eagle Transmission
KRANKSÆT	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant XCR WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EGER	Carbon
DÆK	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EKSTRA	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Pris: 75.439,00 kr.

GEOMETRI

RAMME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Sadelrørslængde (mm)	400	420	465	495
Sadelrørsvinkel	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°
Overrørslængde (mm)	576 574	602 600	624 623	651 650
Kronrørslængde (mm)	90	95	105	115
Kronrørsvinkel	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°
Forgaffel fremspring (rake) (mm)	44	44	44	44
Sti (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2
Akselafstand (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Kædestagslængde (mm)	437 435	437 435	437 435	437 435
Krankboks drop (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Skridthøjde (mm)	769 775	764 771	758 763	751 758
Styrbredde (mm)	780	780	780	780
Frempindslængde (mm)	60	70	70	80
Pedalarmslængde (mm)	170	170	175	175

Alle de anførte specifikationer kan ændres uden varsel.