

ANTHEM ADVANCED SL 0 *



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Raw Carbon
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	RockShox Sid Ultimate 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
SHOCK	RockShox SidLuxe Ultimate, RL damper, Solo Air, TwistLoc Ultimate
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
STEM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SEATPOST	Giant Contact Switch SL dropper S: 110mm travel / 30.9 x 340mm M: 140mm travel / 30.9 x 390mm L: 140mm travel / 30.9 x 390mm XL: 140mm travel / 30.9 x 390mm
SADDLE	Giant Grit SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, Rocker Paddle, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM XX Eagle T-Type AXS
BRAKES	SRAM Motive ULT, hydraulic, SRAM HS2 6 bolt rotors [F]180mm, [R]160mm
BRAKE LEVERS	SRAM Motive ULT
CASSETTE	SRAM XS-1297 Eagle T-Type 10-52T
CHAIN	SRAM XX SL T-Type
CRANKSET	SRAM XX SL Eagle Transmission with Quarq power meter, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant XCR Carbon WheelSystem
HUBS	[F] Giant alloy, 6-bolt [R] Giant Alloy, 120T Helical-Bevel Ratchet Driver, 6-Bolt
SPOKES	Carbon
TIRES	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	Tubeless prepared, 2.4" max tyre size, 34t max chainring size, MRP 1x SL TR2 chain guide

Price: \$17,999.00

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400		420		465		495	
Seat Tube Angle	75.5° 76.0°		75.5° 76.0°		75.5° 76.0°		75.5° 76.0°	
Top Tube Length (mm)	576 574		602 600		624 623		651 650	
Head Tube Length (mm)	90		95		105		115	
Head Tube Angle	66.5° 67.0°		66.5° 67.0°		66.5° 67.0°		66.5° 67.0°	
Fork Rake (mm)	44		44		44		44	
Trail (mm)	116 112.2		115.9 112.2		115.9 112.2		115.8 112.2	
Wheelbase (mm)	1141 1140		1168 1167		1192 1191		1221 1220	
Chain Stay Length (mm)	437 435		437 435		437 435		437 435	
Bottom Bracket Drop (mm)	51 45		51 45		52 45		52 45	
Stack (mm)	602 599		607 603		616 612		626 622	
Reach (mm)	420 425		445 450		465 470		490 495	
Stand Over Height (mm)	769 775		764 771		758 763		751 758	
Stem Length (mm)	60		70		70		80	
Crank Length (mm)	170		170		175		175	

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.