

ANTHEM ADVANCED SL 0

GIANT



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, L, XL
VÄRIT	Gloss Raw Carbon/Matte Raw Carbon
RUNKO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
HAARUKKA	RockShox Sid Ultimate 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
ISKUNVAIMENNIN	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTIT	
OHJAUSTANKO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPIT	SRAM TwistLoc Ultimate
OHJAINKANNATIN	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SATULATOLPPA	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel /
SATULA	Giant Grit SL
POLKIMET	N/A
VOIMANSIIRTO	
VAIHDEVIPU	SRAM AXS Pod, 1x12
ETUVAIHTAJA	N/A
TAKAVAIHTAJA	SRAM XX Eagle Transmission
JARRUT	SRAM Motive ULT, hydraulic, SRAM HS2 6-bolt rotors [F]180mm, [R]160mm
JARRUKAHVAT	SRAM Motive ULT
RATASPAKKA	SRAM XS 1297 Eagle Transmission, 10x52
KETJUT	SRAM XX Eagle Transmission
KAMPISARJA	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant XCR WheelSystem
NAVAT	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
PINNAT	Carbon
RENKAAT	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
LISÄTIEDOT	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Suositus hinta: 10 099,00 €

GEOMETRIA

RUNKO	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Satulaputken pituus (mm)	400	420	465	495
Satulaputken kulma	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°
Vaakaputken pituus (mm)	576 574	602 600	624 623	651 650
Emäputken pituus (mm)	90	95	105	115
Emäputken kulma	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°
Haarukan offset (mm)	44	44	44	44
Trail-mitta (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2
Akseliväli (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Takahaarukan alaputken pituus (mm)	437 435	437 435	437 435	437 435
Keskiön pudotus (mm)	51 45	51 45	52 45	52 45
Stack-mitta (mm)	602 599	607 603	616 612	626 622
Reach-mitta (mm)	420 425	445 450	465 470	490 495
Standover-mitta (mm)	769 775	764 771	758 763	751 758
Ohjaustangon leveys (mm)	780	780	780	780
Ohjainkannattimen pituus (mm)	60	70	70	80
Kammen pituus (mm)	170	170	175	175

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.