

# ANTHEM ADVANCED SL 0

GIANT



## SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Gloss Raw Carbon/Matte Raw Carbon
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VOORVORK	RockShox Sid Ultimate 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
DEMPER	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
ONDERDELEN	
STUUR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
HANDVATTEN	SRAM TwistLoc Ultimate
STUURPEN	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
ZADELPEN	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel /
ZADEL	Giant Grit SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	SRAM AXS Pod, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	SRAM XX Eagle Transmission
REMMEN	SRAM Motive ULT, hydraulic, SRAM HS2 6-bolt rotors [F]180mm, [R]160mm
REMHENDELS	SRAM Motive ULT
CASSETTE	SRAM XS 1297 Eagle Transmission, 10x52
AANDRIJVING	SRAM XX Eagle Transmission
CRANKSET	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant XCR WheelSystem
NAVEN	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPAKEN	Carbon
BANDEN	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRA'S	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Adviesprijs: € 9.499,00

## GEOMETRIE

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis lengte (mm)	400	420	465	495				
Zitbuis hoek	75,5°   76,0°	75,5°   76,0°	75,5°   76,0°	75,5°   76,0°				
Frame Lengte (horizontaal) (mm)	576   574	602   600	624   623	651   650				
Balhoofdbuis Lengte (mm)	90	95	105	115				
Balhoofdbuis Hoek	66,5°   67,0°	66,5°   67,0°	66,5°   67,0°	66,5°   67,0°				
Vork Sprong (mm)	44	44	44	44				
Naloop (mm)	116   112,2	115,9   112,2	115,9   112,2	115,8   112,2				
Wielbasis (mm)	1141   1140	1168   1167	1192   1191	1221   1220				
Liggende achtervork lengte (mm)	437   435	437   435	437   435	437   435				
Bottom Bracket Drop (mm)	51   45	51   45	52   45	52   45				
Stack (mm)	602   599	607   603	616   612	626   622				
Reach (mm)	420   425	445   450	465   470	490   495				
Stand Over Height (mm)	769   775	764   771	758   763	751   758				
Stuur breedte (mm)	780	780	780	780				
Stuurpen Lengte (mm)	60	70	70	80				
Cranklengte (mm)	170	170	175	175				

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.