



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Gloss Raw Carbon/Matte Raw Carbon
OKVIR	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VILICE	RockShox Sid Ultimate 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
AMORTIZER	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTE	
KRMILO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
OPORA KRMILA	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
OPORA SEDEŽA	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel /
SEDEŽ	Giant Grit SL
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM AXS Pod, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM XX SL Eagle Transmission
ZAVORE	SRAM Motive ULT, hydraulic, SRAM HS2 6-bolt rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	SRAM Motive ULT
VERIŽNIK	SRAM XS 1297 Eagle Transmission, 10x52
VERIGA	SRAM XX Eagle Transmission
GONILKE Z VERIŽNIKI	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant XCR WheelSystem
PESTA	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
NAPERE	Carbon
PLAŠČI	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
DODATKI	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	400		420		465		495	
Kot sedežne cevi	75,5° 76,0°		75,5° 76,0°		75,5° 76,0°		75,5° 76,0°	
Top Tube Length (mm)	576 574		602 600		624 623		651 650	
Višina glave okvirja (mm)	90		95		105		115	
Krmilni kot	66,5° 67,0°		66,5° 67,0°		66,5° 67,0°		66,5° 67,0°	
Zamik vpetja osi (mm)	44		44		44		44	
Trail (mm)	116 112,2		115,9 112,2		115,9 112,2		115,8 112,2	
Medosna razdalja (mm)	1141 1140		1168 1167		1192 1191		1221 1220	
Dolžina cevi ob verigi (mm)	437 435		437 435		437 435		437 435	
Bottom Bracket Drop (mm)	51 45		51 45		52 45		52 45	
Oddaljenost zgornje cevi od gonilne osi (mm)	602 599		607 603		616 612		626 622	
Doseg (mm)	420 425		445 450		465 470		490 495	
Višina zgornje cevi (mm)	769 775		764 771		758 763		751 758	
Širina krmila (mm)	780		780		780		780	
Dolžina opore krmila (mm)	60		70		70		80	
Dolžina gonilke (mm)	170		170		175		175	

Vse navedene specifikacije se lahko spremenijo brez obvestila.