

ANTHEM ADVANCED SL 0

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Gloss Raw Carbon/Matte Raw Carbon
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	RockShox Sid Ultimate 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
SHOCK	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
STEM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SEATPOST	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel /
SADDLE	Giant Grit SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM XX SL Eagle Transmission
BRAKES	SRAM Motive ULT, hydraulic, SRAM HS2 6-bolt rotors [F]180mm, [R]160mm
BRAKE LEVERS	SRAM Motive ULT
CASSETTE	SRAM XS 1297 Eagle Transmission, 10x52
CHAIN	SRAM XX Eagle Transmission
CRANKSET	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant XCR WheelSystem
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPOKES	Carbon
TIRES	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400		420		465		495	
Seat Tube Angle	75.5°	76.0°	75.5°	76.0°	75.5°	76.0°	75.5°	76.0°
Top Tube Length (mm)	576	574	602	600	624	623	651	650
Head Tube Length (mm)	90		95		105		115	
Head Tube Angle	66.5°	67.0°	66.5°	67.0°	66.5°	67.0°	66.5°	67.0°
Fork Rake (mm)	44		44		44		44	
Trail (mm)	116	112.2	115.9	112.2	115.9	112.2	115.8	112.2
Wheelbase (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Chain Stay Length (mm)	437	435	437	435	437	435	437	435
Bottom Bracket Drop (mm)	51	45	51	45	52	45	52	45
Stack (mm)	602	599	607	603	616	612	626	622
Reach (mm)	420	425	445	450	465	470	490	495
Stand Over Height (mm)	769	775	764	771	758	763	751	758
Handlebar Width (mm)	780		780		780		780	
Stem Length (mm)	60		70		70		80	
Crank Length (mm)	170		170		175		175	

All specifications listed are subject to change without notice.