

ANTHEM ADVANCED SL 1

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, L, XL
FARVER	Rainbow Black/Rainbow Charcoal
RAMME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORGAFFEL	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
BAGDÆMPER	RockShox SidLux Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTER	
STYR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GREB / STYRBÅND	SRAM TwistLoc Ultimate
FREMPIND	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SADELPIND	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel
SADEL	Giant Grit SL
PEDALER	N/A
GEARGRUPPE	
SKIFTEGREB	SRAM AXS Pod, discrete clamp, 1x12
FORSKIFTER	N/A
BAGSKIFTER	SRAM GX AXS Transmission
BREMSE	Shimano Deore XT BR-M8220, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
BREMSEGREB	Shimano Deore XT BL-M8200
KASSETTE	SRAM XS 1275, 10x52
KÆDE	SRAM GX Transmission
KRANKSÆT	SRAM GX Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant XCR WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EGER	Carbon
DÆK	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EKSTRA	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Pris: 55.499,00 kr.

GEOMETRI

RAMME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Sadelrørlængde (mm)	400	420	465	495				
Sadelrørsvinkel	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°				
Overrørs længde (mm)	576 574	602 600	624 623	651 650				
Kronrørlængde (mm)	90	95	105	115				
Kronrørsvinkel	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°				
Forgaffel fremspring (rake) (mm)	44	44	44	44				
Sti (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2				
Akselafstand (mm)	1141 1140	1168 1167	1192 1191	1221 1220				
Kædestagslængde (mm)	437 435	437 435	437 435	437 435				
Krankboks drop (mm)	51 45	51 45	52 45	52 45				
Stack (mm)	602 599	607 603	616 612	626 622				
Reach (mm)	420 425	445 450	465 470	490 495				
Skridthøjde (mm)	769 775	764 771	758 763	751 758				
Styrbredde (mm)	780	780	780	780				
Frempindslængde (mm)	60	70	70	80				
Pedalarmslængde (mm)	170	170	175	175				

Alle de anførte specifikationer kan ændres uden varsel.