

# ANTHEM ADVANCED SL 1

GIANT



## ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Rainbow Black/Rainbow Charcoal
CUADRO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
HORQUILLA	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
AMORTIGUADOR	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTES	
MANILLAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
PUÑOS	SRAM TwistLoc Ultimate
POTENCIA	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
TIJA DE SILLÍN	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel
SILLÍN	Giant Grit SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS Pod, discrete clamp, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	SRAM GX AXS Transmission
FRENOS	Shimano Deore XT BR-M8220, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
PALANCAS DE FRENOS	Shimano Deore XT BL-M8200
CASSETTE	SRAM XS 1275, 10x52
CADENA	SRAM GX Transmission
JGO. PLATOS Y BIELAS	SRAM GX Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
CAJA DE PEDALIER	SRAM DUB, press fit

RUEDAS	
LLANTAS	Giant XCR WheelSystem
BUJES	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
RADIOS	Carbon
CUBIERTAS	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Precio: 6.499,00 €

## GEOMETRÍA

CUADRO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud del tubo del sillín (mm)	400	420	465	495				
Ángulo del tubo del sillín	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Longitud del tubo superior (mm) (mm)	576	574	602	600	624	623	651	650
Longitud del tubo de dirección (mm) (mm)	90	95	105	115				
Ángulo del tubo de dirección	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Inclinación de la horquilla (mm)	44	44	44	44				
Trail (mm) (mm)	116	112,2	115,9	112,2	115,9	112,2	115,8	112,2
Distancia entre ejes (mm) (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Longitud de la vaina (mm) (mm)	437	435	437	435	437	435	437	435
Caída del eje de pedalier (mm) (mm)	51	45	51	45	52	45	52	45
Stack (mm) (mm)	602	599	607	603	616	612	626	622
Reach (mm) (mm)	420	425	445	450	465	470	490	495
Altura del suelo al tubo (mm) (mm)	769	775	764	771	758	763	751	758
Ancho del manillar (mm) (mm)	780	780	780	780				
Longitud de la potencia (mm) (mm)	60	70	70	80				
Longitud de las bielas (mm) (mm)	170	170	175	175				

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.