

ANTHEM ADVANCED SL 1

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Rainbow Black/Rainbow Charcoal
CUADRO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
TIJERA	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
AMORTIGUADOR	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTES	
MANUBRIO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
POTENCIA	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
POSTE DE ASIENTO	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel
ASIENTO	Giant Grit SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS Pod, discrete clamp, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	SRAM GX AXS Transmission
FRENOS	Shimano Deore XT BR-M8220, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
PALANCAS DE FRENOS	Shimano Deore XT BL-M8200
CASSETTE	SRAM XS 1275, 10x52
CADENA	SRAM GX Transmission
MULTIPLICACIÓN	SRAM GX Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
EJE DE CENTRO	SRAM DUB, press fit

RUEDAS	
RUEDAS	Giant XCR WheelSystem
MAZAS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
RAYOS	Carbon
NEUMÁTICOS	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Precio: \$149,990.00

GEOMETRÍA

CUADRO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud de la Base del Poste de Asiento (mm)	400		420		465		495	
Ángulo de la Base del Poste de Asiento	75.5°	76.0°	75.5°	76.0°	75.5°	76.0°	75.5°	76.0°
Longitud del Tubo Superior (mm)	576	574	602	600	624	623	651	650
Longitud del Telescopio (mm)	90		95		105		115	
Ángulo del Telescopio	66.5°	67.0°	66.5°	67.0°	66.5°	67.0°	66.5°	67.0°
Rake (mm)	44		44		44		44	
Trail (mm)	116	112.2	115.9	112.2	115.9	112.2	115.8	112.2
Distancia entre Ejes (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Longitud de Vaina Inferior (mm)	437	435	437	435	437	435	437	435
Caída del Eje de Centro (mm)	51	45	51	45	52	45	52	45
Stack (mm)	602	599	607	603	616	612	626	622
Reach (mm)	420	425	445	450	465	470	490	495
Altura del Tubo Superior al Suelo (mm)	769	775	764	771	758	763	751	758
Ancho del Manubrio (mm)	780		780		780		780	
Longitud de la Potencia (mm)	60		70		70		80	
Longitud de la Biela (mm)	170		170		175		175	

Todas las especificaciones están sujetas a cambios sin previo aviso.