ANTHEM ADVANCED SL 1

SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VOORVORK	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
DEMPER	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
ONDERDELEN	
STUUR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
HANDVATTEN	SRAM TwistLoc Ultimate
STUURPEN	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
ZADELPEN	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm XL: 140-170mm travel / 30.9 x 530mm
ZADEL	Giant Grit SL
AFMONTAGE	
SHIFTERS	SRAM AXS Pod, discrete clamp, 1x12
ACHTERDERAILLEUR	SRAM GX AXS Transmission
REMMEN	Shimano Deore XT BR-M8220, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
REMHENDELS	Shimano Deore XT BL-M8200
CASSETTE	SRAM XS 1275, 10x52
AANDRIJVING	SRAM GX Transmission
CRANKSET	SRAM GX Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant XCR WheelSystem
NAVEN	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt
SPAKEN	Carbon
BANDEN	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRA'S	tubeless prepared, MRP 1x CS chain guide
LIMITS	
MAXIMALE BANDENVRIJHEID	2.4"
MAXIMALE KETTINGBLADMAAT	34T

Adviesprijs: € 6.999,00

GEOMETRIE

FRAME	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Zitbuis Lengte (mm)	400	420	465	495
Zitbuis Hoek	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°
Frame Lengte (horizontaal) (mm)	576 | 574	602 | 600	624 | 623	651 | 650
Balhoofdbuis Lengte (mm)	90	95	105	115
Balhoofdbuis Hoek	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	116 | 112,2	115,9 | 112,2	115,9 | 112,2	115,8 | 112,2
Wielbasis (mm)	1141 | 1140	1168 | 1167	1192 | 1191	1221 | 1220
Liggende achtervork lengte (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Bottom Bracket Drop (mm)	51 | 45	51 | 45	52 | 45	52 | 45
Stack (mm)	602 | 599	607 | 603	616 | 612	626 | 622
Reach (mm)	420 | 425	445 | 450	465 | 470	490 | 495
Stand Over Height (mm)	769 | 775	764 | 771	758 | 763	751 | 758
Stuur breedte (mm)	780	780	780	780
Stuurpen Lengte (mm)	60	70	70	80
Cranklengte (mm)	170	170	175	175

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.