

ANTHEM ADVANCED SL 1

GIANT



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
RAHMEN	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
GABEL	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
DÄMPFER	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTEN	
LENKER	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIFFE	SRAM TwistLoc Ultimate
VORBAU	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SATTELSTÜTZE	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm XL: 140-170mm travel / 30.9 x 530mm
SATTEL	Giant Grit SL
ANTRIEB	
SCHALTHEBEL	SRAM AXS Pod, discrete clamp, 1x12
SCHALTWERK	SRAM GX AXS Transmission
BREMSSEN	Shimano Deore XT BR-M8220, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
BREMSHEBEL	Shimano Deore XT BL-M8200
KASSETTE	SRAM XS 1275, 10x52
KETTE	SRAM GX Transmission
KURBEL	SRAM GX Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
TRETLAGER	SRAM DUB, press fit

LAUFRÄDER	
FELGEN	Giant XCR WheelSystem
NABE	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt
SPEICHEN	Carbon
REIFEN	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, MRP 1x CS chain guide
LIMITS	
MAX TIRE CLEARANCE	2.4"
MAX CHAINRING SIZE	34T

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Sitzrohrlänge (mm)	400	420	465	495
Sitzrohrwinkel	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°
Oberrohrlänge (mm)	576 574	602 600	624 623	651 650
Steuerrohr-Länge (mm)	90	95	105	115
Steuerrohr-Winkel	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	116 112.2	115.9 112.2	115.9 112.2	115.8 112.2
Radstand (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Kettenstreben-Länge (mm)	437 435	437 435	437 435	437 435
Tretlager-Höhe (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Überstandshöhe (mm)	769 775	764 771	758 763	751 758
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	60	70	70	80
Kurbellänge (mm)	170	170	175	175

Spezifikations-, Preis- und Farbänderungen vorbehalten.