

ANTHEM ADVANCED SL 1

GIANT



SPECIFIKACIJE

OKVIR	
VELIČINE	S, M, L, XL
BOJE	Rainbow Black/Rainbow Charcoal
OKVIR	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VILICA	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
AMORTIZER	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTE	
VOLAN	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
LULA VOLANA	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
CIJEV SJEDALA	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel
SJEDALO	Giant Grit SL
PEDALE	N/A
POGON	
RUČICE MJENJAČA	SRAM AXS Pod, discrete clamp, 1x12
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	SRAM GX AXS Transmission
KOČNICE	Shimano Deore XT BR-M8220, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
RUČICE KOČNICA	Shimano Deore XT BL-M8200
KAZETA	SRAM XS 1275, 10x52
LANAC	SRAM GX Transmission
POGON	SRAM GX Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Giant XCR WheelSystem
NABE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
ŽBICE	Carbon
GUME	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
DODACI	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIJA

OKVIR	S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dužina cijevi sjedala (mm)	400	420	465			
Kut cijevi sjedala	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Dužina gornje cijevi (mm)	576	574	602	600	624	623
Dužina prednje cijevi (mm)	90		95		105	
Kut vilice	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Zakrivljenost vilice (offset) (mm)	44		44		44	
Staza (mm)	116	112,2	115,9	112,2	115,9	112,2
Međuosovinski razmak kotača (mm)	1141	1140	1168	1167	1192	1191
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	437	435	437	435	437	435
Položaj osovine pogona (mm)	51	45	51	45	52	45
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	602	599	607	603	616	612
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	420	425	445	450	465	470
Prekoračna visina (mm)	769	775	764	771	758	763
Širina volana (mm)	780		780		780	
Dužina lule volana (mm)	60		70		70	
Dužina poluge pedale (mm)	170		170		175	

Sve navedene specifikacije podložne su promjeni bez prethodne najave.