

ANTHEM ADVANCED SL 1

GIANT



SPECS

TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Rainbow Black/Rainbow Charcoal
TELAIO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORCELLA	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
AMMORTIZZATORE	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTISTICA	
MANUBRIO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
MANOPOLE	SRAM TwistLoc Ultimate
ATTACCO MANUBRIO	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
REGGISSELLA	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel
SELLA	Giant Grit SL
PEDALI	N/A
SISTEMA DI TRASMISSIONE	
CAMBIO	SRAM AXS Pod, discrete clamp, 1x12
DERAGLIATORE ANTERIORE	N/A
DERAGLIATORE POSTERIORE	SRAM GX AXS Transmission
FRENI	Shimano Deore XT BR-M8220, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
COMANDI FRENO	Shimano Deore XT BL-M8200
PACCO PIGNONI	SRAM XS 1275, 10x52
CATENA	SRAM GX Transmission
GUARNITURA	SRAM GX Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
MOVIMENTO CENTRALE	SRAM DUB, press fit

RUOTE	
CERCHI	Giant XCR WheelSystem
MOZZI	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
RAGGI	Carbon
COPERTONI	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRA	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Prezzo: 7.499,00 €

GEOMETRIA

TELAIO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Lunghezza Tubo Sella (mm)	400	420	465	495				
Angolo Tubo Sella	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°		
Lunghezza Tubo Orizzontale (mm)	576 574	602 600	624 623	651 650				
Lunghezza Tubo Sterzo (mm)	90	95	105	115				
Angolo Sterzo	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°		
Rake Forcella (mm)	44	44	44	44				
Avancorsa (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2				
Interasse (mm)	1141 1140	1168 1167	1192 1191	1221 1220				
Lunghezza Carro Posteriore (mm)	437 435	437 435	437 435	437 435				
Drop Movimento Centrale (mm)	51 45	51 45	52 45	52 45				
Stack (mm)	602 599	607 603	616 612	626 622				
Reach (mm)	420 425	445 450	465 470	490 495				
Altezza stand over (mm)	769 775	764 771	758 763	751 758				
Larghezza Manubrio c/c (mm)	780	780	780	780				
Lunghezza Attacco Manubrio (mm)	60	70	70	80				
Lunghezza Pedivella (mm)	170	170	175	175				

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.