

ANTHEM ADVANCED SL 1

GIANT



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	S, M, L, XL
FARBY	Rainbow Black/Rainbow Charcoal
RÁM	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VIDLICA	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
TLMÍČ	RockShox SidLux Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTY	
RIADIDLÁ	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPY	SRAM TwistLoc Ultimate
PREDSTAVEC	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SEDLOVKA	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel
SEDADLO	Giant Grit SL
PEDÁLE	N/A
POHON	
RADENIE	SRAM AXS Pod, discrete clamp, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	SRAM GX AXS Transmission
BRZDY	Shimano Deore XT BR-M8220, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
BRZDOVÉ PÁKY	Shimano Deore XT BL-M8200
KAZETA	SRAM XS 1275, 10x52
REŤAZ	SRAM GX Transmission
KLUKY	SRAM GX Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
STREDOVÉ ZLOŽENIE	SRAM DUB, press fit

KOLESÁ	
RÁFIKY	Giant XCR WheelSystem
NÁBOJE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
ŠPICE	Carbon
PNEUMATIKY	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
DOPLNKY	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Cena: 7 299 €

GEOMETRIA

RÁM	S	M	L	XL
Dĺžka sedlovej trubky (mm)	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Uhol sedlovej trubky	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°
Dĺžka hornej rámovej trubky (mm)	576 574	602 600	624 623	651 650
Dĺžka hlavovej trubky (mm)	90	95	105	115
Uhol hlavovej trubky	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°
Offset vidlice (mm)	44	44	44	44
Trail (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2
Rázvor (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Dĺžka zadnej stavby (mm)	437 435	437 435	437 435	437 435
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	51 45	51 45	52 45	52 45
Stack - výška riadenia (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Výška rámu od zeme (mm)	769 775	764 771	758 763	751 758
Šírka riaditok (mm)	780	780	780	780
Dĺžka predstavca (mm)	60	70	70	80
Dĺžka kľúku (mm)	170	170	175	175

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.