

ANTHEM ADVANCED SL 1

GIANT



產品規格

車架	
尺寸	S, M
顏色	Rainbow Black/Rainbow Charcoal彩虹黑
車架	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
前叉	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
避震器	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTS	
車把手	Giant Integrated XC, composite, 780mm, 9-degree upsweep
把手帶/套	SRAM TwistLoc Ultimate
豎桿	Giant Integrated XC Carbon 5:60mm, M:70mm
座桿	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm
坐墊	Giant Grit SL
踏板	N/A
DRIVETRAIN	
變速把手	SRAM AXS Pod, discrete clamp, 1x12
前變速器	N/A
後變速器	SRAM GX AXS Transmission
煞車系統	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
煞車把手	Shimano Deore XT BL-M8100
飛輪	SRAM XS 1275, 10x52
鍊條	SRAM GX Transmission
大齒盤	SRAM GX Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET (B B)	SRAM DUB, press fit

輪組	
輪圈	Giant XCR WheelSystem
花鼓	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
輻條	Carbon
外胎	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
其他	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Price: NT\$198,000

車架幾何

車架	S		M	
	LOW	HIGH	LOW	HIGH
座(立)管長 (mm)	400	420		
座(立)管角度	75.5° 76.0°	75.5° 76.0°		
上管長度 (mm)	576 574	602 600		
頭管長度 (mm)	90	95		
頭管角度	66.5° 67.0°	66.5° 67.0°		
前叉 (mm)	44	44		
Trail (mm)	116 112.2	115.9 112.2		
前後輪距 (mm)	1141 1140	1168 1167		
後下叉長度 (mm)	437 435	437 435		
五通下降高度 (mm)	51 45	51 45		
頭碗至五通高度 (mm)	602 599	607 603		
頭碗至五通長度 (mm)	420 425	445 450		
上管至地面高度 (mm)	769 775	764 771		
把手寬 (mm)	780	780		
龍頭長度 (mm)	60	70		
曲柄長度 (mm)	170	170		

*捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。