

ANTHEM ADVANCED SL 2

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, L, XL
FARVER	Mariana Blue/Icicle White
RAMME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORGAFFEL	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
BAGDÆMPER	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTER	
STYR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GREB / STYRBÅND	SRAM TwistLoc Ultimate
FREMPIND	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SADELPIND	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel /
SADEL	Giant Grit
PEDALER	N/A
GEARGRUPPE	
SKIFTEGREB	SRAM Eagle 90 mechanical, 1x12
FORSKIFTER	N/A
BAGSKIFTER	SRAM Eagle 90 Transmission
BREMSE	Shimano SLX BR-M6220, hydraulic, Giant RT66 rotors [F]180mm, [R]160mm
BREMSEGREB	Shimano SLX BL-M6200
KASSETTE	SRAM 70 1270, 10x52
KÆDE	SRAM 70 Transmission
KRANKSÆT	SRAM 90 Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant XCA WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EGER	Sapim
DÆK	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EKSTRA	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Pris: 43.499,00 kr.

GEOMETRI

RAMME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Sadelrørlængde (mm)	400		420		465		495	
Sadelrørsvinkel	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Overrørs længde (mm)	576	574	602	600	624	623	651	650
Kronrørlængde (mm)	90		95		105		115	
Kronrørsvinkel	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Forgaffel fremspring (rake) (mm)	44		44		44		44	
Sti (mm)	116	112,2	115,9	112,2	115,9	112,2	115,8	112,2
Akselafstand (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Kædestagslængde (mm)	437	435	437	435	437	435	437	435
Krankboks drop (mm)	51	45	51	45	52	45	52	45
Stack (mm)	602	599	607	603	616	612	626	622
Reach (mm)	420	425	445	450	465	470	490	495
Skridthøjde (mm)	769	775	764	771	758	763	751	758
Styrbredde (mm)	780		780		780		780	
Frempindslængde (mm)	60		70		70		80	
Pedalarmslængde (mm)	170		170		175		175	

Alle de anførte specifikationer kan ændres uden varsel.