

# ANTHEM ADVANCED SL 2

**GIANT**



## SPECS

FRAME	
<b>SIZES</b>	S, M, L, XL
<b>COLOURS</b>	Mariana Blue/Icicle White
<b>FRAME</b>	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
<b>FORK</b>	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
<b>SHOCK</b>	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTS	
<b>HANDLEBAR</b>	Giant Integrated XC, composite, 780mm, 9-degree upsweep
<b>GRIPS</b>	SRAM TwistLoc Ultimate
<b>STEM</b>	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
<b>SEATPOST</b>	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel /
<b>SADDLE</b>	Giant Grit
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM Eagle 90 mechanical, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	SRAM Eagle 90 Transmission
<b>BRAKES</b>	Shimano SLX BR-M6220, hydraulic, Giant RT66 rotors [F]180mm, [R]160mm
<b>BRAKE LEVERS</b>	Shimano SLX BL-M6200
<b>CASSETTE</b>	SRAM 70 1270, 10x52
<b>CHAIN</b>	SRAM 70 Transmission
<b>CRANKSET</b>	SRAM 90 Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant XCA WheelSystem
<b>HUBS</b>	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
<b>SPOKES</b>	Sapim
<b>TYRES</b>	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
<b>EXTRAS</b>	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

**Price: €6,349.00**

## GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400		420		465		495	
Seat Tube Angle	75.5°   76.0°		75.5°   76.0°		75.5°   76.0°		75.5°   76.0°	
Top Tube Length (mm)	576	574	602	600	624	623	651	650
Head Tube Length (mm)	90		95		105		115	
Head Tube Angle	66.5°   67.0°		66.5°   67.0°		66.5°   67.0°		66.5°   67.0°	
Fork Rake (mm)	44		44		44		44	
Trail (mm)	116   112.2		115.9   112.2		115.9   112.2		115.8   112.2	
Wheelbase (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Chain Stay Length (mm)	437	435	437	435	437	435	437	435
Bottom Bracket Drop (mm)	51	45	51	45	52	45	52	45
Stack (mm)	602	599	607	603	616	612	626	622
Reach (mm)	420	425	445	450	465	470	490	495
Stand Over Height (mm)	769	775	764	771	758	763	751	758
Handlebar Width (mm)	780		780		780		780	
Stem Length (mm)	60		70		70		80	
Crank Length (mm)	170		170		175		175	

All specifications listed are subject to change without notice.