

ANTHEM ADVANCED SL 2

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Mariana Blue
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
SHOCK	RockShox SidLuxe Select+, RL damper, Solo Air, TwistLoc Ultimate
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
STEM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SEATPOST	Giant Contact Switch SL dropper S: 110mm travel / 30.9 x 340mm M: 140mm travel / 30.9 x 390mm L: 140mm travel / 30.9 x 390mm XL: 140mm travel / 30.9 x 390mm
SADDLE	Giant Grit
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Eagle 90, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Eagle 90 T-Type
BRAKES	Shimano SLX BR-M7100, hydraulic, Giant TR-55 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano SLX BR-M7100
CASSETTE	SRAM XS-1270, T-Type 10x52
CHAIN	SRAM Eagle 70 T-Type
CRANKSET	SRAM Eagle 90 T-Type, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	XCA 29 Alloy Wheelsystem
HUBS	[F] Giant alloy, 6-bolt [R] Giant Alloy, 120T Helical-Bevel Ratchet Driver, 6-Bolt
SPOKES	Sapim
TIRES	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	Tubeless prepared, 2.4" max tyre size, 34t max chainring size, MRP CS chain guide

Price: \$9,299.00

GEOMETRY

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	420	465	495
Seat Tube Angle	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°
Top Tube Length (mm)	576 574	602 600	624 623	651 650
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	116 112.2	115.9 112.2	115.9 112.2	115.8 112.2
Wheelbase (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Chain Stay Length (mm)	437 435	437 435	437 435	437 435
Bottom Bracket Drop (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Stand Over Height (mm)	769 775	764 771	758 763	751 758
Stem Length (mm)	60	70	70	80
Crank Length (mm)	170	170	175	175

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.