ANTHEM ADVANCED SL 2



SPECS

FRAME	
SIZES	S, M, L, XL
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
SHOCK	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
STEM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SEATPOST	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm XL: 140-170mm travel / 30.9 x 530mm
SADDLE	Giant Grit
DRIVETRAIN	
SHIFTERS	SRAM Eagle 90 mechanical, 1x12
REAR DERAILLEUR	SRAM Eagle 90 Transmission
BRAKES	Shimano Deore BR-M6220, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano Deore BL-M6200
CASSETTE	SRAM 70 1270, 10x52
CHAIN	SRAM 70 Transmission
CRANKSET	SRAM 90 Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant XCA WheelSystem
HUBS	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt
SPOKES	Sapim
TIRES	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, MRP 1x CS chain guide
LIMITS	
MAX TIRE CLEARANCE	2.4"
MAX CHAINRING SIZE	34T

Recommended Retail Price: $5,600.00

GEOMETRY

FRAME	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Seat Tube Length (inch)	15.7	16.5	18.3	19.5
Seat Tube Angle	75.5° | 76.0°	75.5° | 76.0°	75.5° | 76.0°	75.5° | 76.0°
Top Tube Length (inch)	22.7 | 22.6	23.7 | 23.6	24.6 | 24.5	25.6 | 25.6
Head Tube Length (inch)	3.5	3.7	4.1	4.5
Head Tube Angle	66.5° | 67.0°	66.5° | 67.0°	66.5° | 67.0°	66.5° | 67.0°
Fork Rake (inch)	1.7	1.7	1.7	1.7
Trail (inch)	4.6 | 4.4	4.5 | 4.4	4.5 | 4.4	4.5 | 4.4
Wheelbase (inch)	44.9 | 44.9	46 | 45.9	46.9 | 46.9	48.1 | 48
Chain Stay Length (inch)	17.2 | 17.1	17.2 | 17.1	17.2 | 17.1	17.2 | 17.1
Bottom Bracket Drop (inch)	2 | 1.8	2 | 1.8	2 | 1.8	2 | 1.8
Stack (inch)	23.7 | 23.6	23.9 | 23.7	24.3 | 24.1	24.6 | 24.5
Reach (inch)	16.5 | 16.7	17.5 | 17.7	18.3 | 18.5	19.3 | 19.5
Stand Over Height (inch)	30.3 | 30.5	30.1 | 30.4	29.8 | 30	29.6 | 29.8
Handlebar Width (inch)	30.7	30.7	30.7	30.7
Stem Length (inch)	2.4	2.8	2.8	3.1
Crank Length (inch)	6.7	6.7	6.9	6.9

**All specifications and prices listed are subject to change without notice.*
Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.