

ANTHEM ADVANCED SL 2

GIANT



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, L, XL
VÄRIT	Mariana Blue/Icicle White
RUNKO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
HAARUKKA	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
ISKUNVAIMENNIN	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTIT	
OHJAUSTANKO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPIT	SRAM TwistLoc Ultimate
OHJAINKANNATIN	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SATULATOLPPA	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel /
SATULA	Giant Grit
POLKIMET	N/A
VOIMANSIIRTO	
VAIHDEVIPU	SRAM Eagle 90 mechanical, 1x12
ETUVAIHTAJA	N/A
TAKAVAIHTAJA	SRAM Eagle 90 Transmission
JARRUT	Shimano SLX BR-M6220, hydraulic, Giant RT66 rotors [F]180mm, [R]160mm
JARRUKAHVAT	Shimano SLX BL-M6200
RATASPAKKA	SRAM 70 1270, 10x52
KETJUT	SRAM 70 Transmission
KAMPISARJA	SRAM 90 Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant XCA WheelSystem
NAVAT	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
PINNAT	Sapim
RENKAAT	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
LISÄTIEDOT	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Suositusuhinta: 5 799,00 €

GEOMETRIA

RUNKO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Satulaputken pituus (mm)	400		420		465		495	
Satulaputken kulma	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Vaakaputken pituus (mm)	576	574	602	600	624	623	651	650
Emäputken pituus (mm)	90		95		105		115	
Emäputken kulma	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Haarukan offset (mm)	44		44		44		44	
Trail-mitta (mm)	116	112,2	115,9	112,2	115,9	112,2	115,8	112,2
Akseliväli (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Takahaarukan alaputken pituus (mm)	437	435	437	435	437	435	437	435
Keskiön pudotus (mm)	51	45	51	45	52	45	52	45
Stack-mitta (mm)	602	599	607	603	616	612	626	622
Reach-mitta (mm)	420	425	445	450	465	470	490	495
Standover-mitta (mm)	769	775	764	771	758	763	751	758
Ohjaustangon leveys (mm)	780		780		780		780	
Ohjainkannattimen pituus (mm)	60		70		70		80	
Kammen pituus (mm)	170		170		175		175	

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.