

# ANTHEM ADVANCED SL 2

GIANT



## SPECS

| TELAIO                         |   |
|--------------------------------|---|
| <b>TAGLIE</b>                  | S, M, L, XL   |
| <b>COLORAZIONI</b>             | Mariana Blue/Icicle White   |
| <b>TELAIO</b>                  | Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle     |
| <b>FORCELLA</b>                | RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout                    |
| <b>AMMORTIZZATORE</b>          | RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate  |
| COMPONENTISTICA                |   |
| <b>MANUBRIO</b>                | Giant Integrated XC, composite, 780mm, 9-degree upsweep   |
| <b>MANOPOLE</b>                | SRAM TwistLoc Ultimate  |
| <b>ATTACCO MANUBRIO</b>        | Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm  |
| <b>REGGISSELLA</b>             | Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel / |
| <b>SELLA</b>                   | Giant Grit  |
| <b>PEDALI</b>                  | N/A   |
| SISTEMA DI TRASMISSIONE        |   |
| <b>CAMBIO</b>                  | SRAM Eagle 90 mechanical, 1x12  |
| <b>DERAGLIATORE ANTERIORE</b>  | N/A   |
| <b>DERAGLIATORE POSTERIORE</b> | SRAM Eagle 90 Transmission  |
| <b>FRENI</b>                   | Shimano SLX BR-M6220, hydraulic, Giant RT66 rotors [F]180mm, [R]160mm   |
| <b>COMANDI FRENO</b>           | Shimano SLX BL-M6200  |
| <b>PACCO PIGNONI</b>           | SRAM 70 1270, 10x52   |
| <b>CATENA</b>                  | SRAM 70 Transmission  |
| <b>GUARNITURA</b>              | SRAM 90 Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm   |
| <b>MOVIMENTO CENTRALE</b>      | SRAM DUB, press fit   |

| RUOTE            |  |
|------------------|--|
| <b>CERCHI</b>    | Giant XCA WheelSystem  |
| <b>MOZZI</b>     | [F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt                             |
| <b>RAGGI</b>     | Sapim  |
| <b>COPERTONI</b> | Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless                      |
| <b>EXTRA</b>     | tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide |

Prezzo: 5.499,00 €

## GEOMETRIA

| TELAIO                          | S     |       | M     |       | L     |       | XL    |       |
|---------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|
|                                 | LOW   | HIGH  | LOW   | HIGH  | LOW   | HIGH  | LOW   | HIGH  |
| Lunghezza Tubo Sella (mm)       | 400   |       | 420   |       | 465   |       | 495   |       |
| Angolo Tubo Sella               | 75,5° | 76,0° | 75,5° | 76,0° | 75,5° | 76,0° | 75,5° | 76,0° |
| Lunghezza Tubo Orizzontale (mm) | 576   | 574   | 602   | 600   | 624   | 623   | 651   | 650   |
| Lunghezza Tubo Sterzo (mm)      | 90    |       | 95    |       | 105   |       | 115   |       |
| Angolo Sterzo                   | 66,5° | 67,0° | 66,5° | 67,0° | 66,5° | 67,0° | 66,5° | 67,0° |
| Rake Forcella (mm)              | 44    |       | 44    |       | 44    |       | 44    |       |
| Avancorsa (mm)                  | 116   | 112,2 | 115,9 | 112,2 | 115,9 | 112,2 | 115,8 | 112,2 |
| Interasse (mm)                  | 1141  | 1140  | 1168  | 1167  | 1192  | 1191  | 1221  | 1220  |
| Lunghezza Carro Posteriore (mm) | 437   | 435   | 437   | 435   | 437   | 435   | 437   | 435   |
| Drop Movimento Centrale (mm)    | 51    | 45    | 51    | 45    | 52    | 45    | 52    | 45    |
| Stack (mm)                      | 602   | 599   | 607   | 603   | 616   | 612   | 626   | 622   |
| Reach (mm)                      | 420   | 425   | 445   | 450   | 465   | 470   | 490   | 495   |
| Altezza stand over (mm)         | 769   | 775   | 764   | 771   | 758   | 763   | 751   | 758   |
| Larghezza Manubrio c/c (mm)     | 780   |       | 780   |       | 780   |       | 780   |       |
| Lunghezza Attacco Manubrio (mm) | 60    |       | 70    |       | 70    |       | 80    |       |
| Lunghezza Pedivella (mm)        | 170   |       | 170   |       | 175   |       | 175   |       |

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.